

estimating

MICHOLS



MERICAN SCHULL OF CORRESPONDENCE


CHICAGO ILLINOIS


#### LIBRARY

OF THE


## University of California.

Class









RESIDENCE OF MR. WARREN HICKOX, KANKAKEE, ILL. Frank Lloyd Wright, Architect, Oak Park, Ill. Built in 1992.

# Estimating

#### A Guide to

SYSTEMATIC METHODS IN TAKING OFF QUANTITIES AND MAKING UP ESTIMATES OF COST IN BUILDING OPERATIONS, WITH QUOTA-TIONS OF CURRENT PRICES FOR MATERIALS AND LABOR

By EDWARD NICHOLS
Architect, Boston, Mass.

ILLUSTRATED



CHICAGO
AMERICAN SCHOOL OF CORRESPONDENCE
1908

TH436

## GENERAL

COPYRIGHT 1907 BY
AMERICAN SCHOOL OF CORRESPONDENCE

Entered at Stationers' Hall, London All Rights Reserved

### Foreword

I

N recent years, such marvelous advances have been made in the engineering and scientific fields, and so rapid has been the evolution of mechanical and constructive processes and methods, that a distinct need has been created for a series of *practical* 

working guides, of convenient size and low cost, embodying the accumulated results of experience and the most approved modern practice along a great variety of lines. To fill this acknowledged need, is the special purpose of the series of handbooks to which this volume belongs.

■ In the preparation of this series, it has been the aim of the publishers to lay special stress on the practical side of each subject, as distinguished from mere theoretical or academic discussion. Each volume is written by a well-known expert of acknowledged authority in his special line, and is based on a most careful study of practical needs and up-to-date methods as developed under the conditions of actual practice in the field, the shop, the mill, the power house, the drafting room, the engine room, etc.

These volumes are especially adapted for purposes of self-instruction and home study. The utmost care has been used to bring the treatment of each subject within the range of the com-

mon understanding, so that the work will appeal not only to the technically trained expert, but also to the beginner and the self-taught practical man who wishes to keep abreast of modern progress. The language is simple and clear; heavy technical terms and the formulæ of the higher mathematics have been avoided, yet without sacrificing any of the requirements of practical instruction; the arrangement of matter is such as to carry the reader along by easy steps to complete mastery of each subject; frequent examples for practice are given, to enable the reader to test his knowledge and make it a permanent possession; and the illustrations are selected with the greatest care to supplement and make clear the references in the text.

The method adopted in the preparation of these volumes is that which the American School of Correspondence has developed and employed so successfully for many years. It is not an experiment, but has stood the severest of all tests—that of practical use—which has demonstrated it to be the best method yet devised for the education of the busy working man.

• For purposes of ready reference and timely information when needed, it is believed that this series of handbooks will be found to meet every requirement.



#### Table of Contents

Variation in Prices—Profit—Percentage—Duplication of Parts— Transportation—Approximate and Detailed Estimates—Estimating by

. . . Page 1

PRELIMINARY PRINCIPLES . . . . . .

the Square; by Quantities-Preparatory Steps-Units-Rules and
Tables-Measurement of Lines and Surfaces-Areas and Solid Con-
tents of Solids.
STANDARD PRICES OF LABOR AND MATERIALS Page 13
Scale of Wages in Various Trades-Excavation-Stonework (Cut
Stone, Granite, Limestone, Window Sets, Sandstone, Setting of Cut
Stone, Marble, Bluestone, Seam-Faced Granite)—Brickwork (Mortar,
Face Brick)—Concrete—Chimneys—Flue-Lining—Mason's Supplies—
Cellar Columns—Earthen Drain-Pipe—Standard Vitrified Pipe—Car-
pentry-Board Measure-Lumber (Dimension, Floor and Finish, Inside
Door-Frames)—Calculating the Frame—Floors—Outside Walls—
Shingling-Roofing-Studding-Windows-Doors-Inside Finish-
Window-Frames-Stairs-A Day's Work-Cost of Labor (by the
Square; by the Piece)-Exterior Finish-Piazzas and Porches-Con-
ductors-Hardware-Nails-Roofing (Shingles, Slate, Tiles, Metal,
Composition, Gutters and Conductors)-Plastering-Lathing-Paint-
ing-Spreading Power of Paints-Heating System (Hot-Air, Steam,
Hot-Water)—Registers, Piping, Radiators, etc.—Plumbing—Drainage
-Water Supply (Boiler, Waste-Cocks, etc.)-Capacity of Cisterns and
Tanks — Sinks — Lavatories — Laundry Trays — Gasfitting — Electric
Work (Wiring, Switches, Bells).
MAKING A DETAILED ESTIMATE
Methods of Estimating-Staking-Out and Setting Batter-Boards-
Water Supply during Construction—Excavation—Stonework—Plaster-
ing Walls with Cement-Cesspools, Dry Wells, and Drains-Brick-
work - Flue-Linings - Concreting - Plastering - Carpentry Work-
Stairs—Hardware—Heating—Plumbing—Electric Wiring—Electric
Lighting Fixtures—Painting—Schedules (Analysis of Carpentry
Work)—Memoranda for Heating Estimate—Location Sheet of Electric
Outlets.
Outlets.





FRONT AND REAR VIEWS OF RESIDENCE OF MR. H. T. LOOMIS, MAGNOLIA DRIVE, CLEVELAND, OHIO

Watterson & Schneider, Architects, Cleveland, Ohio.

Cost, about \$35,000. First-Story Walls of McCausland Brick, Made at Akron, Ohio. Roofs of Combination Red Tile.

## CALIFORNIA

## **ESTIMATING\***

#### PART I

Introductory. The ability to estimate may be considered as the dividing line between the journeyman and the master builder, for, no matter how skilful a mechanic may become, he can never "hang out his shingle" and invite patronage in his distinctive line of work, unless he becomes able to make reliable estimates of material and labor to be furnished. To do this something more than mere accuracy and quickness in figures or a mastery of mathematics is needed; namely: experience and judgment, an understanding of the more or less complicated details which go to make up a building, and a knowledge of current prices and discounts in the trade. It is the object of this paper to point the way toward the acquirement of such of these needs as may be imparted by words or figures; that is, to put in condensed form some of the common methods by which estimates are made up, and to point out some of the things which are to be avoided.

Prices. As prices of labor and materials are constantly shifting, those quoted in this paper must be taken only as proportionate, to be used in comparison with known quantities and methods. All prices given are as current in Boston, Mass., in December, 1906, and are subject to immediate change. On account of the variableness in price of labor and materials, it is better, in general, to make estimates on the basis of days or hours, and quantities of materials, so that they may be used for comparison in future work. To this end all estimates should be carefully labelled and filed away for future reference. This should be done whether the bids were successful or otherwise. If a successful bid, there will arise a good opportunity to compare the estimates of cost of the different items, with the actual cost of execution; and if a bid fails to win the job, satisfaction and experience may be gained by noting the items which may have been priced too high or too low. This data may be of great service in preparing future estimates, especially in the comparisons between estimated and actually executed work.

<sup>\*</sup>There is no such a thing as a universal or permanent standard price for anything. Prices vary in different localities at the same time, and in the same locality at different times. The estimator must therefore acquaint himself with local market conditions in every case.

Catalogues. Catalogues and price lists of all standard articles are easily obtained and should be kept at hand, properly indexed, for ready reference, as they contain a great deal of specific information. For close figuring, however, it will not do to rely upon these prices, as the amounts of trade discounts are not always included. These vary greatly from time to time, and often there are two or more discounts, a trade discount, a cash discount, and a variation in discounts made by different merchants, all of which the contractor must become aware of to obtain bottom prices.

All data of this sort should be carefully tabulated for constant reference, in such a form that it may be easily revised and kept, so far as possible, up to date.

The manner and time of payments is a matter to be considered in this connection, as it will permit the contractor to take advantage of cash discounts, which often make a great difference in the cost of certain materials.

**Profit.** To the actual price of labor and materials must be added the profit and this will need careful consideration. A common method is to add a lump sum to the estimated cost of labor and materials, varying with locality and customer, with the probable sharpness of competition and the circumstances of the contractor. This is a careless method, as it leaves no means for future comparison and no certain knowledge of just what the profits of a given job are.

Percentage. A better way is to base the profits upon a percentage of the estimated cost. This will vary, in ordinary cases, from ten to fifteen per cent, ten per cent being the least that should be expected on any work, and this is not enough for small contracts of two or three thousand dollars; but for large work, where there is a great duplication of parts and processes, it will be enough in most cases. Some contractors, whose workmen are required to perform especially skilful labor, figure fifteen per cent on all labor and ten per cent on materials.

Duplicate Parts. The matter of duplication is an important factor in estimating, as a considerable saving is often made if large quantities of material, either worked or unworked, are required; this is especially true in manufactured parts, such as doors and windows, columns, balustrades, etc. Modern machines are capable of duplication with astonishing rapidity, and workmen can put together

similar parts more quickly and cheaply than variable members.

Transportation. The distance of the work from the shop of the contractor, or from centers of manufacture, will effect the cost to a marked degree, as much time is consumed in teaming and especially in handling material a number of times.

If communication between the works and the building site can be established by water, it will usually save considerable expense for freight and handling, with perhaps less risk of damage, and consequently less expense for crating and boxing. A careful study should be made of the means of transportation to each different building site from the shop, the office, and the mill, and the data kept for future reference, subject to varying rates and conditions, to change of seasons, and amounts to be transported.

These are some of the more important matters which require preliminary consideration as affecting all estimates, and are only a small part of the real questions involved, as different localities and customs require different treatment, and numerous questions will arise to confront the contractor, all of which may be successfully met, as we have seen, by the exercise of care and judgment.

Methods. Estimates are formed by many and varying methods, depending upon the degree of accuracy required, the capability of the contractor, and the character of the building. A broad division may be made between approximate estimates and accurate detailed estimates, only the latter of which should be considered when it is the intention to actually carry out the work under a definite contract.

Approximate Estimates. Approximate estimates are obtained with varying degrees of accuracy by several methods, the most convenient and reliable of which is the system of *cubing*; i.e., the cubical contents of the proposed building is obtained and multiplied by a given price per cubic foot. This rate is obtained by careful comparison of the plans and requirements with similar buildings which have been erected under conditions as like as possible to the conditions under which the proposed building can be erected.

Several methods are used to determine the cubical units, depending upon the size and shape of the proposed building. One method is to multiply the square feet in the plan of the building by the height from half-way the depth of foundations to half-way up the roof. Another system uses the height from the bottom of the

Oller

foundation, and another obtains the actual cubical contents. Any of these may be used if the data for comparison is obtained in the same way, but all are subject to important variations which experience and judgment alone will determine. For instance, if the contour of the building is very uneven, with low portions, such as porches and sheds, and high portions, such as towers and cupolas, these must either be omitted from the whole and compared separately, or a lump sum be added or subtracted according to the size and elaboration of these members.

Another variation arises in the size of rooms, giving a ratio of partitions and division walls which is not constant, and of course a large building with many duplicate parts will require a different rating from a smaller one, so that the method of estimating by cubing is at best approximate, and its degree of accuracy depends largely upon the experience and judgment of the contractor. Even long experience will afford no safe-guard against unusual elaboration of interior or exterior, so that cube rates can only be applied to buildings of ordinary character, and comparisons are only reliable between buildings of like description and uses, as the treatment of even the same materials will vary largely in buildings of varying uses.

The height of the building will not increase the cube rate proportionately, unless the internal voids are alike, although it is certain that the higher one builds from the ground, the more time and expense it requires to put the material in place, to say nothing of thicker walls and necessarily heavier construction.

Estimating by the Square. A convenient method of estimating is by the square of one hundred surface feet. This is especially applicable to office buildings, schools, mills, stables, and all buildings where the floors are few in number or similar in plan. For one story buildings the price per square is taken to include the roof, walls, floor, and foundations, but for buildings of two or more stories the price per square should be taken separately for each floor, the lower floor being priced to include the foundations and the top floor to include the roof.

This method of estimating by the square is not so accurate as by cubical contents, but the results are often more convenient and adaptable, because the tabulation of the square area of the various floors may be easily reduced to terms of accommodation for public buildings or shops. For instance, a given floor area in a school house means accommodation for a certain number of pupils; in a church, a certain number of sittings; in factories for the manufacture of staple goods, a certain number of machines and operatives.

This unit of accommodation is sometimes carried further, and, by the reverse process, made the basis of another method of estimating the approximate cost of such buildings as the above mentioned, i.e., schools, churches, factories, hospitals, etc. This is also a method by comparison, the known data being supplied by previous experience or calculation, and it is often valuable as a means of determining the approximate cost of buildings necessary to accommodate a given number of individuals or machines, even before any definite plans have been drawn. All of these methods are approximate, with varying degrees of accuracy, and should never be advanced as accurate, or used as the basis of a contract, unless the contractor has had a long and varied experience and feels absolutely certain of his judgment, or unless a proper margin is added for possible variations.

Estimating by Quantities. The only sure and correct method of estimating is by taking off the actual quantities in detail and carrying out the prices accurately with the cost of labor, the percentage for profit, and contingencies added.

For this, accurate and complete drawings and specifications are necessary to give the absolute quantity and quality of materials and labor. The various items are then taken off, similar portions grouped, the amount of labor estimated, and a complete and classified schedule prepared and priced at current rates; the cost of transportation, board of men, and any other contingencies noted, a percentage of profit added, and a sum total reached which should be correct if faithfully done.

This, of course, takes considerable time, but is well worth the expense and trouble if a definite contract is to be made.

Preparation. In order to estimate to a sufficient degree of accuracy, some things other than the possession of plans and specifications are necessary. A visit to the site should be made, to ascertain the nature of the soil, the levels of the lot, the distance from railroad or wharf, the condition of the roads, if a long haul is necessary, and the preparation of the site necessary to receive and dispose of materials. Some knowledge should be obtained of the nature of

the sub-soil, the presence of ledges or water below the surface which will require especial or costly treatment, etc. Often a deposit of sand will be found upon the site which will not only save carting away of material excavated, but, if of proper quality, it may be used for the work. Such items are constantly occurring so that a knowledge of existing conditions will be of great advantage to the estimator.

Regarding underground conditions, there is always an element of chance, as the most thorough examination will not always reveal hidden perils; the author knows of a case where a mason had contracted for the building of a sewer, and was in a fair way to make a good profit, when a narrow vein of quicksand was uncovered, to overcome which not only took away all the anticipated profit but caused a severe loss to the contractor besides.

Ground water is another source of danger and it will be well for the contractor to closely examine his contract, to see to what extent he is to furnish protection from this source, as a vein of water which may have been temporarily stopped or diverted by the operation of building, will sometimes unexpectedly make its presence known during or after the completion of the work, when it may become a source of great annoyance and expense to the contractor if he has agreed to insure a waterproof job. Numerous illustrations could be given of the danger from unforeseen causes which can at best be only partially obviated by the most careful examination.

In order to accurately take off a building either by quantities, square or cube, a good knowledge of arithmetic is necessary; and, while we may assume that the reader already possesses this knowledge, it may be well to include some of the essential rules of that branch of arithmetic which is known as mensuration.

This consists primarily in the science of obtaining definite data regarding given figures or surfaces, such as areas, solids, capacity, linear dimensions, and comparisons of bodies.

**Definitions.** The *area*, or superficial dimension of any figure is the measure of its surface, without regard to its thickness or any other dimension.

The *cubical contents* of any figure is the measure of its solidity, or whole capacity, and has reference to the three dimensions, length, breadth, and thickness.

If the figure is considered as hollow, then the cubical contents becomes its capacity or capability of containing matter.

The *linear dimension* of a figure is expressed by its length in a direct line in any direction and has no regard to breadth or thickness.

Units. The application of these dimensions is made by fixing a unit by which the figure may be compared and the required dimension obtained; thus, for calculating the area of a figure the unit is usually a square, one side of which is the unit of length, and the area becomes the square measure of the figure.

This is expressed in common terms by square inch, square foot, square yard, or any other given unit and the measure of the surface is computed by obtaining the number of these square units which are contained in the figure, the process being called squaring.

In a similar manner the cubical contents or solidity of a figure is obtained by computing the number of cubical units which it contains, which is called cubing it.

Rules. Numerous rules have been adopted for obtaining these dimensions when given dimensions are known, and a tabulation of some of the more important and useful of these follows, by means of which it is hoped that the student may be able to solve most of the ordinary problems which will arise in common practice.

## RULES AND TABLES TABLE OF MULTIPLES

Circumference	of a circle	=	diameter $\times$ 3.1416
Area	of a circle	=	square of the radius $\times$ 3.1416
Area	of a circle	=	square of the diameter $\times$ 0.7854
Area	of a circle	=	square of the circumference $\times$ 0.07958
Area	of a circle	=	half the circumference $\times$ half the
			diameter
Radius	of a circle	=	circumference $\times$ 0.159155
Radius	of a circle	=	square root of the area $\times$ 0.56419
Diameter	of a circle	=	circumference $\times$ 0.31831
Diameter .	of a circle	=	square root of area $\times$ 1.12838
Side of an inso	cribed square	=	diameter $\times$ 0.7071
Side of an insc	eribed square	=	circumference ×. 0.2251
Side of an equ	al square	=	diameter $\times$ 0.8862
Area of a trian	ng!e	=	base by ½ the altitude

Area of an ellipse = product of both diameters  $\times$  .7854 Surface of a sphere = circumference  $\times$  diameter Surface of a sphere = square of the diameter  $\times$  3.1416 Surface of a sphere = square of the circumference  $\times$  0.3183 Solid contents of a sphere = surface  $\times \frac{1}{6}$  of its diameter Solid contents of a sphere = cube of diameter  $\times$  0.5236 of a sphere = square root of surface  $\times$  0.56419 Diameter Diameter of a sphere = cube root of solidity  $\times$  1.2407 Circumference of a sphere = cube root of solidity  $\times$  3.8978

pyramid = area of base  $\times \frac{1}{3}$  altitude Surface of a cube = six  $\times$  area of one side Area of trapezoid = altitude  $\times \frac{1}{2}$  sum of parallel sides

Solid contents of a cone or

Note-Volumes of similar solids are to each other as the cubes of their similar lines.

#### MEASURE OF LINES AND SURFACE

1. To find the area of a parallelogram: Rule—Multiply the length by the breadth or perpendicular height. See Fig. 1






Fig. 1.

- 2. To find the area of a triangle: Rule—Multiply the base by half the altitude. See Fig. 2.
- 3. To find the hypothenuse of a right-angled triangle when the base and perpendicular are known: Rule—Add together the square of the known sides and extract the square root of the sum. See Fig. 3.
- 4. To find one side of a right-angled triangle when the hypothenuse and the other side are known: Rule—From the square of the hypothenuse subtract the square of the given side, and





Area=bcx2ad

Fig. 2.






Fig. 3.



 $b = \sqrt{a^2 - c^2}$   $c = \sqrt{a^2 - b^2}$ 

Fig. 4.




Area=(acx bf)+(acx de)

Fig. 5.

the square root of the remainder will be the other side. See Fig. 4.

- 5. To find the area of a trapezium: Rule—Divide the figure into triangles by drawing a diagonal and the sum of the areas of these triangles will be the area of the trapezium. See Fig. 5.
- 6. To find the area of a trapezoid: Rule—Add the two parallel sides and mutliply by one-half the perpendicular distance between them. See Fig. 6.



7. To find the area of a regular polygon: Rule—Multiply one side by half its perpendicular distance from the center, and this product by the number of sides.

Table of Multiples to Compute Measurements of Regular Polygons, the Side of the Polygon Being Unity

		A	В	C	D
NAME OF POLYGON	No. of Sides	AREA	RADIUS OF CIRCUM- SCRIBING CIRCLE	LENGTH	RADIUS OF INSCRIBED CIRCLE
Triangle	3	0.433013	0.5773	1.732	0.2887
Tetragon	4	1	0.7071	1.4142	0.5
Pentagon	5	1.720477	0.8506	1.1756	0.6882
Hexagon	6	2.598076	1	1	0.866
Heptagon	7	3.633912	1.1524	0.8677	1.0383
Octagon	8	4.828427	1.3066	0.7653	1.2071
Nonagon	9	6.181824	1.4619	0.684	1.3737
Decagon	10	7.694209	1.618	0.618	1.5383
Undecagon	11	9.36564	1.7747	0.5634	1.7028
Dodecagon	12	11.196152	1.9319	0.5176	1.866


- 8. To find the area of a regular polygon when the length of a side only is given: *Rule*—Multiply the square of the side by the number opposite the name of the polygon in Column A.
  - 9. To find the radius of a circumscribing circle when the

length of a side only is given: Rule-Multiply the length of a side of

the polygon by the number in Column B.


10. To find the length of side of a polygon that is contained in a given circle, when the radius of the circle is known: *Rule*—Multiply the radius of the circle by the number opposite the name of the polygon in Column C.

11. To find the radius of a circle that can be inscribed in a given polygon, when the length of a side is given: Rule—Multiply the length of a side of the



Area  $(ab)^2(cd)^2$  x.7854 Fig. 8.

polygon by the number opposite the name of the polygon in Column D.



## Lateral Area= 2 acx(b+c+d+e+f+g)

Fig. 9.

12. To find the area of an irregular polygon: Rule—Divide the polygon into triangles and add the areas of all the triangles. Fig. 7.



Fig. 10. Frustrum of Pyramid.

- 13. To find the area of a ring included between the circumferences of two concentric circles: Rule—Square the diameters and multiply difference between the squares by .7854. Fig. 8.
- 14. To find the area of an ellipse: Rule—Multiply the two axes together and the product multiplied by .7854 will be the area.
- 15. To find the circumference of an ellipse: Rule-Square

#### AREAS OF CIRCLES

-						-	
Size	AREA	Size	AREA	Size	AREA	Size	AREA
1	0.0123	10	78.54	30	706.86	65	3318.3
î	0.0491	1 2	86.59	31	754.76	66	3421.2
3	0.1104	11	95.03	32	804.24	67	3525.6
î	0.1963	1/2	103.86	33	855.30	68	3631.6
5	0.3067	12	113.09	34	907.92	69	3739.2
3	0.4417	1/2	122.71	35	962.11	70	3848.4
	0.6013	13	132.73	36	1017.8	71	3959.2
1°	0.7854	1/2	143.13	37	1075.2	72	4071.5
	0.9940	14	153.93	38	1134.1	73	4185.3
î	1.227	1/2	165.13	39	1194.5	74	4300.8
3	1.484	15	176.71	40	1256.6	75	4417.8
1	1.767	1 1	188.69	41	1320.2	76	4536.4
מן- ושיר ממנט ביין מליים ביין מליים	2.073	16	201.06	42	1385.4	77	4656.0
3	2.405	1 1	213.82	43	1452.2	78	4778.3
7	2.761	17	226.98	44	1520.5	79	4901.6
2°	3.141	1 1	240.52	45	1590.4	80	5026.5
	3.976	18	254.46	46	1661.9	81	5153.0
1234	4.908	1	268.80	47	1734.9	82	5281.0
3	5.939	19	283.52	48	1809.5	83	5410.6
3	7.068	1	298.64	49	1885.7	84	5541.7
	8.295	20	314.16	50	1963.5	85	5674.5
141224	9.621	1 1	330.06	51	2042.8	86	5808.8
3	11.044	21	346.36	52	2123.7	87	5944.6
4	12.566	1 1	363.05	53	2206.1	88	6082.1
1	15.904	22	380.13	54	2290.2	89	6221.1
5	19.635	1 1	397.60	55	2375.8	90	6361.7
1	23.758	23	415.47	56	2463.0	91	6503.8
6	28.274	1 1	433.73	57	2551.7	92	6647.6
7	33.183	24	452.39	58	2642.0	93	6792.9
7	38.484	1 1	471.43	59	2733.9	94	6939.7
1	44.178	25	490.87	60	2827.4	95	7088.2
8	50.265	26	530.93	61	2922.4	96	7238.2
1/2	56.745	27	572.55	62	3019.0	97	7389.8
9	63.617	28	615.75	63	3117.2	98	7542.9
1/2	70.882	29	660.52	64	3216.9	99	7697.7
2	. 0.002				The second secon		

To find the circumference of a circle when diameter is given, multiply the given diameter by 3.1416.

To find the diameter of a circle when circumference is given, multiply the given circumference by .31831.

the two axes and multiply the square root of half their sum by 3.1416.

#### AREAS OF SOLIDS

- 16. To find the lateral surface of a prism: Rule—Multiply the perimeter of the base by the altitude.
- 17. To find the lateral surface of a regular pyramid: Rule—Multiply the perimeter of the base by one-half the slant height. Fig. 9.
- 18. To find the lateral surface of the frustrum of a regular pyramid: *Rule*—Multiply the perimeters of the two ends by one-half the slant height. Fig. 10.

#### SOLID CONTENTS

- 19. To find the solid contents of a pyramid: Rule—Find the area of the base and multiply this by  $\frac{1}{3}$  height.
- 20. To find the solid contents of a cylinder: Rule—Multiply the area of the base by the height.
- 21. To find the solid contents of a cone: Rule—Multiply the area of the base by  $\frac{1}{3}$  of the height.
- 22. To find the solid contents of a sphere: Rule—Multiply the cube of the diameter by .5236.

#### SCALE OF WAGES

The item of cost of labor, on construction of any kind, is at best a variable quantity, dependent to a large degree upon competition, demand, and labor organization.

The cost of labor is steadily on the increase, while the hours of labor are continually decreasing. The tendency in both directions operates to a certain degree to lessen the effective power of labor, so that the amount of work done in a day is not what it represented a few years ago.

The various schedules given in the following pages are based upon the current price of labor in Boston, Mass., in 1906, and while this is likely to be upset somewhat by a general advance in 1907, there is not likely to be a great difference for some time. Blank spaces are left in these columns so that the student or contractor can fill in local or varying prices of labor.

Wages, Per Day of Eight Hours, in Various Trades, Boston, Mass., 1906

\$3.285
4.507.=
4.807
2.405
5.007.
3.005
4.50
2.50
4.00
4.80
2.60

Roofers	\$3.504.
Roofers' Helpers	2.253.50
Steam Fitters	4.409.50
Steam Fitters' Helpers	2.25
Plumbers	4.407
Plumbers' Helpers	1.50
Gas Fitters	4.40
Gas Fitters' Helpers	2.25
Electricians	- 3.60
Painters	3.00

#### · EXCAVATION

Many considerations, seen and unforeseen, enter into the cost of excavations, of which the unforeseen conditions can, at best, be only judged of, making it more important that known circumstances should be carefully considered. Among these may be mentioned the varying kinds of soil and rock, the depth to which the excavation can be carried without shoring, the distance to which the excavated material is to be carried, and whether pumping or bailing will be necessary. Material excavated to a depth of six feet can be thrown on to the surface, but below this depth a stage will be necessary, or else it must be carted or wheeled out.

In taking off quantities for excavation, work in trenches should be kept separate from large areas, as the cost will be greater on account of lack of room for working.

Where the nature of the soil is uncertain, borings should be made or test pits dug, not only to reveal the character of the material, but to determine the depth at which "hard pan" is to be found. This is especially necessary when the specifications call for the foundations of any structure to be carried to hard pan, without reference to the drawings, or when no definite depth of footing is shown.

In the absence of full instructions, it is best to figure to excavate a foot outside of all walls or footings, to give ample working room; and trenches for pipes, etc., should be enough wider than the pipe to allow of working all around. Hollows should be made where hubs rest, so as to give a full bearing for the pipe.

In taking quantities in irregular ground, the plot should be divided into a number of definite squares and the contents of each square taken separately. See Fig. 11.

Cost of Excavating. The cost of excavating varies in different localities and under differing conditions, no two cases agreeing in details or in execution. The governing factors are experience and judgment. Excavating is usually priced by the cubic yard and will average about as follows:

Picking—12 cu. yds. per day at \$2.40	\$0.20
Throwing out—12 cu. yds. per day at \$2.40	.20
Wheeling 50 ft. away	.10
	\$0.50

Excavations in clay or very hard soil may cost from \$0.50 to \$1.00 while rock excavations will cost from \$2.00 to \$10.00, or more,

according to the nature and position of the rock. Re-filling and packing around walls will cost usually from  $\frac{1}{4}$  to  $\frac{1}{2}$  of the price of earth excavations. Excavation of sand or loose gravel, which can be




Fig. 11. Division of plot.

done by means of a horse scraper, will cost \$0.30 per cu. yd.

Pile Foundations. The cost of piling varies with the nature of the soil and the length of pile necessary. Taking a 30-ft. pile as an average length, then piles 30 ft. long, driven and cut off level to receive footings, will cost \$3.50 to \$4.00 per pile.

#### STONE WORK

Stone walls are figured either by the perch or the cubic yard. In taking off a stone foundation, it is customary to take the corners twice, that is, each different face of the wall is measured from out to out, thus doubling the corners. This makes up for the extra labor of laying up the corners.

The cost of a perch of rubble foundations laid in Rosendale cement mortar, 1 to 3, may be taken as follows:

1 perch of stone	\$1.25
$\frac{1}{2}$ barrel cement at \$1.20	.60
$\frac{1}{6}$ load sand at 1.75	.29
$\frac{1}{3}$ day, mason at 4.50	1.50
day, laborer at 2.40	.60
Total cost per perch	\$4.24

A perch of rubble wall laid in Portland cement mortar, 1 to 3, will cost:

1 perch of stone		\$1.25
½ barrel Portland cen	nent at \$2.10	1.05
1/6 load sand	at \$1.75	.29
1/3 day, mason	at 4.50	1.50
½ day, laborer	at 2.40	.80
Total cost per p	perch	\$4.89

Cut Stone. Cut stonework is figured by the cubic foot, the prices differing according to the amount of labor involved in the cutting; and this will depend somewhat upon the nature of the stone, a hard stone being more expensive to prepare than a soft one. The principal kinds of stone used in building are granite, limestone, sandstone, marble, and bluestone.

Granite. Granite is one of the hardest stones to quarry and prepare, and, on account of its cost it is not so freely used as limestone or marble. Granite in rough blocks from the quarry will cost 45 to 60 cents a cubic foot, the cutting of beds and joints will cost 25 cents for each square foot of surface so treated. If the face is pitched off to a line with rock face, it will cost 25 cents per square foot, while hammering in 8-cut work will cost 70 cents per square foot. Quincy granite will cost, in the rough, about double this, or \$1.20 per cubic foot; the cutting will cost one-third more.

From this data we may deduce the following scale:

Granite, in rough blocks at quarry,	per cu. ft.	\$0.60
Add for beds and joints	per sq. ft.	.25
Add for rock face, pitched off to a line,	per sq. ft.	.25
Add for 8-cut work	per sq. ft.	.70

Hence the facing of an average wall with 8 inches of granite


will cost, if the stones are about 2 feet x 3 feet, or 6 surface feet in each block:

Stock, 4 cu. ft.	at .60	\$2.40
Beds and end joints $2\frac{2}{3}$ sq	. ft. at .25	.67
Rock face 6 sq. ft.	at .25	1.50
Cost of 6 superficial	ft	\$4.57
or $76\frac{1}{6}$ cents per square for		W 2101

If the same were finished in 8-cut work, the cost of finishing the

surface would be 70 cents a square foot instead of 25 cents, making the cost per square foot 45 cents more, or about \$1.21 a square foot.

Limestone. Limestone is used to a large extent, especially in conjunction with brick, for trimmings for various kinds of buildings. Limestone will cost at the quarry about 30 cents a cubic foot; this will apply to Indiana limestone only. Lake Superior redstone will cost 35 cents; Ohio sandstone 50 cents. In estimating



Ohio sandstone, 50 cents. In estimating, Fig. 12. Limestone Window Set. about 20 per cent should be added for waste, 5 per cent quarry waste, and 15 per cent for cutting waste:

#### \* Prices of Common Shapes of Limestone

Water table, 8 in. x 12 in.	per lineal foot	\$1.50
Steps, 7 in. x 14 in. without nosing,	per lineal foot	1.50
Steps, 7 in. x 14 in. with nosing	per lineal foot	2.50
Door sills, 8 in. x 12 in.	per lineal foot	1.25
Window sills, 5 in. x 12 in.	per lineal foot	1.00
Window sills, 5 in. x 8 in.	per lineal foot	.75
Window caps, 4 in. x 10 in.	per lineal foot	.70
Window caps, 8 in. x 12 in.	per lineal foot	1.00
Wall coping, 5 in. x 20 in.	per lineal foot	1.50
Platforms and large slabs, 6 in. thic	ck, per sq. ft.	2.00

\*Window Sets. A common use of limestone is in the form of window sets, consisting of a flat arch in three pieces with keystone, and a light sill, as shown in Fig. 12.

<sup>\*</sup>These prices are based on a freight charge of \$0.55 per cu. ft. to Boston.

The freight on Lake Superior stone is .55

The freight on Ohio stone

The rise of these caps is about 10 inches, and the rise of the sill 5 inches. These sets for an average sized window, say 4-foot opening, will cost for a 4-inch reveal \$10, and for an eight-inch reveal \$15.

Sandstone. The cost of dressed sandstone is about 10 per cent more than that of limestone.

Setting. The cost of setting cut stone may be taken at 15 cents a running foot for window trimmings and ashlar work, and




Fig. 13. Seam-Faced Granite Wall.

20 cents for platforms, water table, steps, etc. Trimming and fitting at the building will cost about 10 cents per cubic foot.

The foregoing prices are based upon quarry-men's wages at \$2.50 per day, and stone cutters' wages at \$4.00 per day.

Much of the cutting and finishing of stone is done by machinery, so that the question of wages will not enter into the preparation of the stock so largely as in many other branches.

Marble. A more expensive stone to use is marble, which can be obtained in a variety of colors, in different parts of the country. The price of marble differs in different localities but for general purposes

may be taken as about double the figures which we have quoted for limestone.

Bluestone. Bluestone is used in the East mainly for flagging, copings, etc., but is used to a considerable extent for building, in Central and Western sections. The price of bluestone flagging 3 inches thick with trimmed joints and face planed and dressed, will be 65 cents a square foot; with natural face, 35 cents to 45 cents. Bluestone ashlar 8 inches thick with natural face and dressed joints, will cost \$1.00 per square foot, and 15 cents a square foot for setting.

Seam-Faced Granite. In some localities granite, lying in upturned strata with open weathered seams, is to be obtained. This is used for facing walls in ashlar work, being set on edge in the wall with the seam-face showing; this will cost, in place, 4-inch to 8-inch thick, from 60 cents to 75 cents a superficial foot. See Fig. 13.

#### **BRICKWORK**

Brickwork is usually estimated by the thousand bricks, but is sometimes priced by the cubic foot at 40 cubic feet to a thousand. A mason in one day will lay from 800 to 1,000 common bricks, or 300 to 400 face bricks.

The number of bricks in a wall may be found by multiplying the superficial area by  $7\frac{1}{2}$  for each 4 inches of the thickness of the wall. Openings of the size of ordinary windows are generally deducted, but very small openings will cost more to make than the deduction. An allowance for breakage should be made of 5 per cent.

Mortar. Bricks are laid in mortar made of lime or cement, according to the strength required. Lime mortar should not be used in damp situations, or where great strength is required. The difference in cost of lime and cement mortar is so little that cement mortar is generally used.

The building laws of some cities require brick work to be laid in cement mortar for a certain part of the height.

Cement mortar makes a darker joint, but where a white joint is required it can be obtained, without loss of strength, by using Portland cement and lime mortar.

Cost. The cost of brickwork by the thousand in various kinds of mortar may be analyzed as follows:

In 1-3 lime mortar,	
1,900 bricks	\$ 9.00
3 bu. lime at \$.36 per bu.	1.08
$\frac{1}{2}$ load of sand at \$1.75 per load	.88
10 hours, mason at \$.60 per hour	6.00
10 hours, tender at \$.30 per hour	3.00
	\$19.96
In 1-3 Rosendale cement mortar:	
1,000 bricks	\$9.00
$1\frac{1}{2}$ bbl. Rosendale cement at \$1.20	1.80
$\frac{1}{2}$ load sand	.88
10 hours, mason at \$.60 per hour	6.00
10 hours, tender at \$.30 per hour	3.00
	\$20.68
In 1-3 Portland cement mortar:	
1,000 bricks	\$ 9.00
$1\frac{1}{4}$ bbl. Portland cement at \$2.10	2.62
$\frac{1}{2}$ load sand at \$1.75	.88
10 hours, mason at \$.60 per hour	6.00
10 hours, tender at \$.30 per hour	3.00
	\$21.50

From these tables we may deduce an approximate estimate in round numbers as follows:

1,000 bricks laid in 1 – 3 lime mortar	\$20.00
1,000 bricks laid in 1 – 3 cement mortar	21.00
1.000 bricks laid in 1-3 Portland cement mortar	22.00

So that, on a job of ordinary size, the difference between lime and cement mortar ought not to be considered, where cement mortar will give assurance of greater stability.

Face Bricks. Face bricks in great variety, are to be had either plain or moulded, and in a variety of colors. On ordinary face brickwork a mason with tender will lay about 300 to 400 bricks in a day.

Faced bricks cost from \$25.00 to \$50.00 per thousand; a good average brick can be secured for \$32.00. This will make the price for a thousand, laid, about as follows:

1,000 face bricks	\$32.00
$1\frac{1}{4}$ bu. lime at \$.36	.45
$\frac{1}{2}$ load fine sand at \$1.75	.88
3 days, mason at \$4.80	14.40
$1\frac{1}{2}$ days, tender at \$2.40	3.60
	\$51.33

From this we find that 1,000 face bricks can be laid in the wall for \$51.33 of which \$33.33 goes for stock and \$18.00 for labor.

Enameled bricks are to be had in various colors, white and buff being the most common. These bricks cost from \$50.00 to \$60.00 per M.

Concrete. Concrete is used to a great extent now for footings, walls, piers, etc. The cost of concrete is not a great deal different from stone for foundations and if there is uncovered a deposit of suitable sand and gravel, as is sometimes the case, it can be put in at a less price than a granite footing.

Concrete with a reinforcement of steel is used in various forms for piers, floors, and walls.

The cost of a cubic yard of concrete, using the proportion of 1-3 and 6, may be summarized as follows:

1 bbl. Portland cement	\$2.10
3 bbl. sand	.75
6 bbl. broken stone	2.00
Mason, 2 hours at \$.60 per hour	1.20
Laborer, 4 hours at \$.30 per hour	1.20
	\$7.25

Cellar concrete 3 inches thick will cost \$.60 to \$.75 per square yard in place. Concrete of Rosendale cement can be put in at less cost, being for foundation walls about \$6.00 per cubic yard; for piers \$6.50 per cubic yard.

#### MISCELLANEOUS DATA

#### CHIMNEYS

Chimneys may be quickly estimated by the lineal foot of height, as follows:

1 flue 8	in. x	8 in.	per	foot	\$0.90	with	flue	lining	\$1.10
1 " 8	in. x	12 in.	per	foot	1.00	."	"	"	1.25
1 " 12	in. x	12 in.	per	foot	1.20	"	"	"	1.50
2 flues 8	in. x	8 in.	per	foot	1.40	66	"	"	1.80
2 " 8	in. x	12 in.	per	foot	1.75	"	"	"	2.20

#### FLUE LINING

Net price per foot, outside dimensions.							
$4\frac{1}{2}$ in. x $8\frac{1}{2}$	inches	\$.10	81/2	in. x	$17\frac{1}{2}$	inches	\$.32
$4\frac{1}{2}$ in. x 13	"	.16	13	in. x	13	"	.30
$8\frac{1}{2}$ in. x $8\frac{1}{2}$	"	.16	13	in. x	18	"	.42
$8\frac{1}{2}$ in. x 13	66	.22	18	in. x	18	"	.70
For openings	s add or	ne-third.				-	

#### MASONS' SUPPLIES

\$ 2.10 per bbl.
1.20 " "
1.15 " "
1.05 " "
1.20 " "
1.60 " "
$.01\frac{1}{4}$ per lb.
$.01\frac{1}{2}$ " "
$.03\frac{1}{2}$ " "
35.00 per M.
35.00 " "
.25 per bush.
1.50 each
1.25 "
.50 "
k .75 "
6.00 "
2.00 "

Metal Corner Bead	\$0.04 per ft.
Iron Rim and Cover, 20 in. diam	neter 3.50 each
" " 18 in. "	3.00 "
" " " 15 in. "	2.50 "

#### CELLAR COLUMNS

For cellar supports, in place of brick piers, pipe columns consisting of a steam pipe filled with cement, under a patent, are coming into general use in many localities.

These columns cost less, and take up less room than a brick pier of equal strength. The prices are as follows:

SIZE,	7 Fr.	8 FT.	9 Fr.	10 Ft.
3 in.	\$1.65	\$1.90	\$2.20	\$2.65
$3\frac{1}{2}$ in.	1.90	2.20	2.65	3.15
4 in.	2.75	3.25	3.80	4.40
$4\frac{1}{2}$ in.	4.00	5.00	5.50	6.00
5 in.	5.00	5.85	6.65	7.55
6 in.	6.00	6.95	8.00	9.30

#### EARTHEN DRAIN PIPE

For sewer and cesspool connections and general drainage, earthen vitrified drain pipes are used. These are laid in cement and, if well below frost or danger of breaking, make a more durable pipe than cast iron, besides being much less costly.

#### Net Price of Standard Vitrified Pipe

INSIDE DIAMETER	PRICE PER FOOT	BENDS AND CURVES	WEIGHT PER FOOT	
2 in.	\$0.05	\$0.17	6 lbs.	
3 in.	.05	.17	8 "	
4 in.	.07	.23	10 "	
5 in.	$.08\frac{3}{4}$	.30	12 "	
6 in.	.10	.38	16 "	
8 in.	.17	.70	24 "	
10 in.	.26	1.00	34 "	
12 in.	.35	1.40	45 "	
15 in.	.47	1.90	67 "	
18 in.	.60	2.38	86 "	

#### CARPENTRY

The Carpenter-Work of a building includes, in general, the skeleton or frame, if a wooden building, the floor timbers, studs of partitions and walls, rafters, the covering in of the frame, with its exterior finish and clapboards, siding or shingles, the flooring, furring, grounds, and beads. This practically covers the constructive woodwork or carpentry proper, while to the term joinery belongs the outside and inside finish, windows and doors, sheathing and dado, stairs and fixtures.

In many sections the general term carpentry covers all woodworking and covering, while in others the distinction between the carpenter and the joiner is more distinctly drawn.

For the purposes of this work it will not be necessary to hold this distinction, and so for convenience, the term carpentry will be used to cover all branches of woodworking.

Two distinct elements enter into the carpenter-work of any structure; the *Material* and the *Labor*, and the cost of both is subject to fluctuation to a great extent. The trend in both is in the direction of increased cost in varying degrees in different localities, but the state of the market in both labor and materials is never quiescent, so that any printed prices must be considered as comparative only, and must be carefully compared with local and known data before being accepted as accurate or final.

The material with which the carpenter works, consists in the main of three principal divisions, the *Frame*, the *Covering*, and the *Finish*, and each of these has further subdivisions as will be noted.

Board Measure. All lumber which has not been wrought or moulded, is sold by "board measure" that is, the stock in each piece is reduced to a unit of a square foot of board one inch thick. This is called board measure and is expressed by the abbreviation B. M. Prices of lumber are usually rated by the thousand feet, so that the expression "Twenty-five dollars a thousand" means twenty-five dollars for a thousand square feet of stock one inch thick. To reduce stock of greater thickness than one inch, to its equivalent in board measure, several rules may be used.

A convenient method is to divide the product of the width and thickness in inches by 12, and multiply by the length in feet.

# TABLE OF BOARD MEASURE

Size in Inches				1	LENG	тн і	N FE	ET	. 12	W	+:	
	10	12	. 14	16	18	20	22	24	26	28	30	32
2 x 3	5	6	7	8	9	10	11	12	13	14	15	16
2 x 4 2 x 5	$\frac{6\frac{2}{3}}{8\frac{1}{3}}$	8	$9\frac{1}{3}$ $11\frac{2}{3}$	$10\frac{2}{3}$ $13\frac{1}{3}$	12 15	$13\frac{1}{3}$ $16\frac{2}{3}$	$14\frac{2}{3}$ $18\frac{1}{3}$	16 20	$17\frac{1}{3}$ $21\frac{2}{3}$	$18\frac{2}{3}$ $23\frac{1}{3}$	$\frac{20}{25}$	$\frac{21\frac{1}{3}}{26\frac{2}{3}}$
$2 \times 6$	10	12	14	16	18	$\frac{10^{3}}{20}$	22	24	$\frac{213}{26}$	$\frac{23_{3}}{28}$	30	$\frac{20_{3}}{32}$
2 x 7	113	14	$16\frac{1}{3}$	183	21	$23\frac{1}{3}$	$25\frac{2}{3}$	28	$30\frac{1}{3}$	$32\frac{2}{3}$	35	371
2 x 8	131	16	$18\frac{2}{3}$	$21\frac{1}{3}$	24	$26\frac{2}{3}$	$29\frac{1}{3}$	32	$34\frac{2}{3}$	$37\frac{1}{3}$	40	$42\frac{2}{3}$
2 x 9	15	18	21	24	27	30	33	36	39	42	45	48
2 x 10 2 x 12	$\frac{16\frac{2}{3}}{20}$	$\frac{20}{24}$	$\frac{23\frac{1}{3}}{28}$	$\frac{26\frac{2}{3}}{32}$	30 36	$33\frac{1}{3}$ $40$	$\frac{36\frac{2}{3}}{44}$	40	$\frac{43\frac{1}{3}}{52}$	$\frac{46\frac{2}{3}}{56}$	50 60	531
2 x 12 2 x 14	$\frac{20}{23\frac{1}{3}}$	28	$\frac{20}{32\frac{2}{3}}$	$\frac{32}{37\frac{1}{3}}$	42	$46\frac{2}{3}$		56	603	$65\frac{1}{3}$	70	$\frac{64}{74\frac{2}{3}}$
2 x 16	263	32	$37\frac{1}{3}$	$42\frac{2}{3}$	48	$53\frac{1}{3}$	$51\frac{1}{3}$ $58\frac{2}{3}$	64	691	743	80	851
3 x 4	10	12	14	16	18	20	22	24	26	28	30	32
3 x 5	$12\frac{1}{2}$	15	$17\frac{1}{2}$	20	$22\frac{1}{2}$	25	$27\frac{1}{2}$	30	$32\frac{1}{2}$	35	$37\frac{1}{2}$	40
3 x 6 3 x 7	15	18	21	24 28	27	30	33	36	39	42	45	48
3 x 7 3 x 8	$\frac{17\frac{1}{2}}{20}$	$\begin{array}{c} 21 \\ 24 \end{array}$	$\frac{24\frac{1}{2}}{28}$	28 32	$\frac{31\frac{1}{2}}{36}$	35 40	$\frac{38\frac{1}{2}}{44}$	42 48	$\frac{45\frac{1}{2}}{52}$	49 56	$\frac{52\frac{1}{2}}{60}$	56 64
3 x 9	223	27	311	36	401	45	493	54	583	63	673	72
3 x 10	25	30	35	40	45	50	55	60	65	70	75	80
3 x 12	30	36	42	48	54	60	66	72	78	84	90	96
3 x 14	35	42	49	56	63	70	77	84	91	98	105	112
3 x 16 4 x 4	40	48 16	$\frac{56}{18\frac{2}{3}}$	$\frac{64}{21\frac{1}{3}}$	72 24	$ \begin{array}{c c} 80 \\ 26\frac{2}{3} \end{array} $	$\frac{88}{29\frac{1}{3}}$	$\frac{96}{32}$	104	112	120	$128 \\ 42\frac{2}{3}$
4 x 4 4 x 5	$13\frac{1}{3}$ $16\frac{2}{3}$	20	$23\frac{1}{3}$	$26\frac{2}{3}$	30	$\frac{20_{3}}{33_{3}^{1}}$	$36\frac{2}{3}$	40	$ \begin{array}{r} 34\frac{2}{3} \\ 43\frac{1}{3} \end{array} $	$\frac{37\frac{1}{3}}{46\frac{2}{3}}$	40 50	$\frac{42_{3}}{53_{3}^{1}}$
4 x 6	20	24	28	32	36	40	44	48	52	56	60	64
4 x 7	$23\frac{1}{3}$	28	323	371	42	463	$51\frac{1}{3}$	56	603	651	70	$74\frac{2}{3}$
4 •x 8	263	32	371	423	48	$53\frac{1}{3}$	$58\frac{2}{3}$	64	$69\frac{1}{3}$	$74\frac{2}{3}$	80	851
4 x 9	30	36	42	48	54	60	66	72	78	84	90	96
4 x 10 4 x 12	$\frac{33\frac{1}{3}}{40}$	40 48	$\frac{46\frac{2}{3}}{56}$	$\frac{53\frac{1}{3}}{64}$	$\begin{array}{c c} 60 \\ 72 \end{array}$	66 <sup>2</sup> / <sub>3</sub>	$\begin{vmatrix} 73\frac{1}{3} \\ 88 \end{vmatrix}$	80 96	$\frac{86^{2}}{104}$	$93\frac{1}{3}$ $112$	$\frac{100}{120}$	$\frac{106\frac{2}{3}}{128}$
4 x 14	463	56	651	743	84	931		112		$130\frac{2}{3}$		1491
6 x 6	30	36	42	48	54	60	66	72	78	84	90	96
6 x 8	40	48	56	64	72	80	88	96	104	112	120	128
6 x 10	50	60	70	80	90	100	110	120	130	140	150	160
6 x 12 6 x 14	60 70	72 84	98	96 112	108 126	120 140	132 154	144 168	$\begin{array}{c} 156 \\ 182 \end{array}$	168 196	$\frac{180}{210}$	196 224
6 x 16	80	96	112	128	144	160	176	$\frac{108}{192}$	208	$\frac{190}{224}$	$\frac{210}{240}$	$\frac{224}{256}$
8 x 8	531	64	743	851	96	1063	$117\frac{1}{3}$	128		$149\frac{1}{3}$		1703
8 x 10	$66\frac{2}{3}$	80	931/3	$106\frac{2}{3}$	120	$133\frac{1}{3}$	1463	160	1733	$186\frac{2}{3}$	200	$213\frac{1}{3}$
8 x 12	80	96	112	128	144	160	176	192	208	224	240	256
8 x 14 10 x 10	$93\frac{1}{3}$ $83\frac{1}{3}$	112 100	1303			1863	205	224	2423	261	280	2983
10 x 10 10 x 12	100	120	140	160	150 180	200	$183\frac{1}{3}$ $220$	$\frac{200}{240}$	$\frac{216\frac{3}{3}}{260}$	$     \begin{array}{r}       233\frac{1}{3} \\       280     \end{array} $	250 300	$\frac{266\frac{2}{3}}{320}$
10 x 14	1163	140	1631		210	$233\frac{1}{3}$		280		3263		$373\frac{1}{3}$
10 x 16	$133\frac{1}{3}$	160	1863		240	$266\frac{2}{3}$	2931	320	3463			4263
12 x 12	120	144	168	192	216	240	264	288	312	336	360	384
12 x 14	140	168	196	224	252	280	308	336	364	392	420	448
12 x 16 14 x 14	160 1634	192 196	$\begin{vmatrix} 224 \\ 228\frac{2}{3} \end{vmatrix}$	$256 \\ 26\frac{1}{3}1$	288 294	3262	$352$ $359\frac{1}{3}$	384 392	416	448	480	512
14 x 16	1863	224	2611	$20\frac{1}{3}$ $29\frac{2}{3}$ $8$		3731	$410\frac{2}{3}$	392	4243	$457\frac{1}{3}$ $522\frac{2}{3}$	560	$522\frac{2}{3}$ $597\frac{1}{3}$
	-003		1 3	30	1	13.03	1 3	110	1003	3	300	3

Example. How many feet, B. M., are there in a joist 2 in. x 9 in., 20 ft. long?

$$\frac{2 \times 9}{12} \times 20 = 30 \text{ ft. B. M.}$$

When the sizes are fractional, or produce a product not easily divided by 12, the operation may sometimes be simplified by varying the process and multiplying the length in feet, and the thickness and width in inches together, and dividing the whole product by 12.

*Example*. How many feet are there in a joist  $2\frac{1}{2}$  in. x 9 in., 16 ft. long?

$$\frac{16 \times 2\frac{1}{2} \times 9}{12} = 30 \text{ ft. B. M.}$$

## MISCELLANEOUS PRICES OF LUMBER

#### LUMBER

Dimension spruce lumber up to 9 inches of	depth will cost a	t
present per M., board measure.	\$26.00	1
10-inch stock, per M.	30.00	
For long lengths, add per M.	2.00	
Hemlock boarding	24.00	
Spruce boarding	25.00	
Spruce boarding matched	27.00	
Spruce upper floor	45.00	
Extra shingles	4.00	
Clear shingles	3.50	
Spruce clapboards	50.00	
Siding cypress	30.00	
Drop or novelty siding	55.00	
Laths	5.00	
Georgia pine timbers 12 in.	35.00	
Georgia pine timbers 14 in.	40.00	
Georgia pine timbers 16 in.	50.00	
FLOORS AND FINISH		
Georgia pine, heart face rift	\$70.00	

45.00

Georgia pine, common rift

Maple flooring	\$ 55.00
Quartered oak flooring 125.00 to	150.00
North Carolina pine, rift stock	40.00
North Carolina pine, slash stock	33.00
FINISH	
Georgia pine	\$ 45.00
Cypress No. 1	80.00
Cypress No. 2	75.00
Oak, plain	90.00
Oak, quartered	120.00
Birch	65.00
Whitewood	52.00
Ash	55.00
Elm	40.00
INSIDE DOOR FRAMES	
2 ft. 8 in. x 6 ft. 8 in.	. \$1.00
2 ft. 10 in. x 6 ft. 8 in.	1.10
3 ft. 0 in. x 7 ft. 0 in.	1.15
For transom bars add	
TOI Hallsom Dats add	.75

Calculating the Frame. In taking off the rough frame of a house for the purposes of estimating, the most accurate method is to take a schedule of every piece of timber from the framing plans, but as it often happens that the estimates are asked for from the general drawings, before framings are made, it has become the custom in many sections to estimate the cost of the walls and floors by the square of 100 superficial feet, making separate allowance for sills, girders, plates, and other large timbers.

If it is desired to take off the frame separately in the absence of framing plans the following data may be of use.

The sills of an ordinary house will usually be from 6 in. x 6 in. to 6 in. x 10 in., girders from 6 in. x 8 in. to 8 in. x 10 in., and floor joists from 2 in. x 8 in. to 3 in. x 12 in. generally 16 in. on centers. Wall studding of outside frame and bearing partitions will usually be 2 in. x 4 in. - 16 in. on centers. Studding of clos-

ets and light walls will usually be 2 in. x 3 in., plates 4 in. x 4 in. and 4 in. x 6 in., sometimes two 2 in. x 4 in. doubled, rafters from 2 in. x 6 in. to 2 in. x 12 in. and 18 in. to 24 in. on centers.

In taking off the frame, the sills and plates will of course be measured by the linear feet in the outside wall. The position of the main bearing partitions will usually give the number and location of the girders. Studs are doubled at openings and at corners, and fireplaces and stair openings will call for timbers of a large size, say from 6 in. to 8 in. width.

Assuming that the joists are 16 in. on centers, the number of joists on a floor will be given by taking  $\frac{3}{4}$  of the length of the building in feet, and adding one joist. The number of studs in the outside frame at 16 in. on centers may be found by taking  $\frac{3}{4}$  of the number of lineal feet in the outside of the building, adding one stud for each corner, and one for each door and window. To this must be added any gables or bay windows or other projections. Three quarters of the number of lineal feet of partitions will give the number of studs in the inside frame at 16 in. on centers. This allows for doubling of studs at openings and corners.

For the number of rafters take the length of the building divided by the distance of the rafters apart and add 1, this gives the number of pairs of rafters if a plain gable roof, while the number of rafters in a hip roof can be found by dividing the whole distance around the building by the distance apart.

Cost of Frame. Spruce lumber is generally used for framing, but Georgia pine must sometimes be used for large girders.

The cost of spruce lumber is from \$26.00 to \$28.00 per M., for sizes 9 in. and under; \$30.00 for 10 in. stock, with a corresponding increase for large sizes. Hard pine lumber, 12 in. and under, will cost \$35.00 per M.; 14 in. sizes \$40.00; 16 in. sizes \$50.00, and so on. Hard pine from the South by shipload will cost about \$5 00 less per M.

The labor of framing sills, girders, etc., will cost about \$10.00 per M.; plates, rafters, etc. \$12.00. From this we estimate that a section of sill 30 ft. long, containing 90 ft. B. M. will cost as follows:

\$3.24

Dividing this by 30, the length in feet, we get  $10\frac{8}{10}$  cents, or about 11 cents a running foot. In this same way the posts, girts, and other special timbers may be figured.

Floors. Having disposed of the large timbers separately we can now take up the floors by the *square of 100 feet*. An analysis of this gives us a result as follows:

Cost of a Square of Flooring:

Joists 2 in. x 9 in., 16 in. on centers, 1121 ft.

001010 = 111. 12 0 111., 10 111. 011 00110010, 11=2 10.	
B. M. at \$26.00	\$2.92
Labor, per square of 100 sq. ft.	1.50
Nails	.10
Bridging	.50
Under floor, 100 ft. Hemlock at \$24.00	2.40
Waste \( \frac{1}{3} \) of stock	.80
Labor	.75
Nails, 5 lbs. at 3 cents per lb.	.15
Strapping for ceiling 1 in. x 2 in., 16 in. on centers	.40
Nails	.10
Labor	1.00
Upper floor, 100 ft. of Spruce at \$40.00	4.00
Waste	1.30
Labor	1.50
Nails	.15
Paper, labor, and stock	.25
Total per square	\$17.82

In the same way we may estimate the cost of the walls as follows: Outside Walls, boarded:

Studding 2 in. x 4 in., 16 in. on centers,	
50 ft. B. M. at \$26.00	\$ 1.30
Waste ½ stock	.43
Nails	.25
Labor, per square, studding	1.50
Beads and grounds	.25
Boarding, 100 ft. hemlock at \$24.00	2.40
Waste 4 stock	.60
Labor per square, boarding	.75
Nails	.15
Total cost per square	* \$ 7.63

Nails Labor on shingling per square Total cost of shingling  Roofing with 2 in. x 6 in. rafters spaced 20 in. on centers will cost 2 in. x 6 in. rafters 20 in. on centers at \$26.00 \$1.5 Waste \frac{1}{4} Labor 2.0	50 5 18 54 t:
Nails Labor on shingling per square  Total cost of shingling  Roofing with 2 in. x 6 in. rafters spaced 20 in. on centers will cost 2 in. x 6 in. rafters 20 in. on centers at \$26.00 \$1.5  Waste \frac{1}{4} Labor  2.1	5 18 54 t:
Labor on shingling per square  Total cost of shingling  Roofing with 2 in. x 6 in. rafters spaced 20 in. on centers will cost 2 in. x 6 in. rafters 20 in. on centers at \$26.00 \$1.5 Waste $\frac{1}{4}$ .3 Labor 2.0	18 54 t:
Total cost of shingling \$6.3  Roofing with 2 in. x 6 in. rafters spaced 20 in. on centers will cost 2 in. x 6 in. rafters 20 in. on centers at \$26.00 \$1.5  Waste \( \frac{1}{4} \) Labor 2.0	t:
Roofing with 2 in. x 6 in. rafters spaced 20 in. on centers will cos 2 in. x 6 in. rafters 20 in. on centers at \$26.00 \$1.5 Waste \frac{1}{4} 3 Labor 2.0	t:
2 in. x 6 in. rafters 20 in. on centers at \$26.00 \$1.5  Waste \( \frac{1}{4} \)  Labor 2.0	66
2 in. x 6 in. rafters 20 in. on centers at \$26.00 \$1.5  Waste \( \frac{1}{4} \)  Labor 2.0	66
Waste $\frac{1}{4}$ .3 Labor 2.0	0
	9
NT 11	0
Nails .1	0
Boarding 2.4	0
Waste .6	0
Labor 1.0	0
Nails .1	5
Total cost per square \$8.2	20
Inside studding ready for lathing will cost:	
Studs, 2 in. x 4 in., 16 in. on centers, 50 ft. B. M. at \$26. \$1.3	
Waste ½ stock	
Nails .1	
Labor, per square	
Beads and grounds .4	0
Total cost per square \$4.0	0
Windows of average size in place will cost approximately:	
Window frame \$1.2	0
Sashes 3 ft. x 5 ft. 1.7	5
Blinds 1.0	0
Blind fastenings .1	5
Weight, 30 lbs. at $1\frac{1}{4}$ cents per lb.	8
Sash cord, 20 ft. at 1 cent per ft2	0
Sash fast	5
Inside casings, 20 ft. at $3\frac{1}{2}$ cents per ft	2007
Stop beads, 16 ft. at $1\frac{3}{4}$ cents per ft.	
Labor, 8 hours at 41 cents per hour 3.2	
Total cost of window in place \$9.1	9

Inside doors of average size will cost, complete:	
Door 2 ft. 8 in. x 6 ft. 8 in. x 1½ in. pine, to paint	\$2.40
Frame	1.00
Casings	1.33
Threshold	.15
Nails	.05
Hardware	1.25
Labor, 8 hours at 41 cents	3.28
Total cost of door in place	\$9.46
Rift hard pine upper floors will cost, per square of 1	
Rift hard pine flooring, 100 ft. B. M. at \$65.00	\$ 6.50
Waste and matching $\frac{1}{3}$ of stock	2.16
Labor	2.00
Nails, 5 lbs. at 3 cents per lb.	.15
Paper	.25
Total cost of floor per square	\$11.06
Approximate cost per square ft.	11 cents
Finishing with shellac and wax	3 cents
Total per square foot finished	14 cents
Quartered oak floor, per square ft.	25 cents
Finishing with shellac	4 cents
Total cost per square foot	29 cents
A common front door will cost:	
Door 3 ft. 4 in. x 7 ft. 0 in. x $1\frac{7}{8}$ in.	\$ 5.75
Frame	4.50
Plate glass	2.50
Casings, 20 ft. at 4 cents	.80
Hinges	.68
Lock and knobs	4.50
Labor	4.00
Total cost of door	\$22.73

A pair of sliding doors, fitted complete, will average about as follows:

2 doors 3 ft. 0 in. x 7 ft. 0 in. x 13 in. each	\$6.00
44 feet casings, at 4½ cents	1.98
40 feet grounds, at 1 cent	.40
40 feet stop beads, at 2 cents	.80
Astragal	1.00
Chafing strip	.20
Lock	4.50
Hangers and track	4.50
Sheathing pocket, 84 ft. at 40 cents	3.36
Labor, 40 hours at 41 cents	16.40
Total cost of doors	\$39.14

These are some of the principal parts of a house analyzed and will serve to show how the cost of any portion may be obtained by dividing it into parts and pricing each portion by itself.

Following are some miscellaneous details of carpenter work: Two carpenters working in pairs can put up in a day about

300 ft. B. M. of studding.

300 ft. B. M. of rafters.

600 ft. B. M. of floor joist.

800 ft. B. M. of wall or roof boarding.

600 ft. B. M. of matched boarding.

500 ft. B. M. of diagonal matched boarding.

# MISCELLANEOUS ITEMS

## CELLAR WINDOW

Frame	\$1.50
Sash	1.20
Hardware	.15
Labor	.50
	\$3.35
CELLAR DOORS	
Stock door, 2 ft. 8 in. x 6 ft. 8 in. x $1\frac{1}{2}$ in.	\$2.25
Frame	1.00
Finish, 36 ft. $4\frac{1}{2}$ in. finish	1.62

Threshold	\$0.15
Hardware	.85
Labor	3.00
	8.87
Paper on walls under clapboards or shingles per square:	
Paper	\$0.20
Laying	.05
	\$0.25

Inside Finish. Inside finish in white wood or cypress, cost in place:

	00 10
8 in. base board with 2 in. moulding, per running ft.	\$0.12
4 ft. wainscot of narrow sheathing, per running ft.	.40
Plain wall sheathing, per square foot	.05
$3\frac{1}{2}$ in. cap for wainscot	.06
2 in. picture moulding	06
4 in. chair rail	.07
3 ft. panelled dado, per sq. ft.	.35
1 case of 3 drawers complete	8.00

Finishing Stock. White wood or cypress stock which has been moulded will cost one cent for every square inch of section a foot long, less a trade discount, which at present is 30 per cent off, so that a 5 in. casing will cost 5 cents per foot less 30 per cent, or  $3\frac{1}{2}$  cts. per foot.

2	
Casings, 5 in.	$\$0.03\frac{1}{2}$
Base, 8 in.	$.05\frac{1}{2}$
Plinth blocks, 5 in. x 8 in. x $1\frac{3}{8}$ in.	. 05
Corner blocks 5 in. x 5 in. x $1\frac{1}{8}$ in.	.05
Mouldings $\frac{7}{10}$ cent per sq. in. of section	
Stock pattern stair rail $2\frac{1}{2}$ in. x $2\frac{3}{4}$ in., per foot	.17
Balusters, 1 <sup>3</sup> / <sub>8</sub> each	.09
Newels, 5 in. stock pattern	5.00
Newels, 6 in. stock pattern	6.00
Plate rail and picture moulding per foot	.09
Picture moulding per foot	$.01\frac{1}{2}$ to $.03$
Stock drawer case, 3 drawers	3.50
Panelled draw case, 5 drawers	13.00



Inside Doors five	cross panels in	pine to paint
2 ft. 8 in. x 6	ft. 8 in. $x 1\frac{1}{2}$ in.	\$2.40
2 ft. 10 in. x 6	ft. 10 in. x $1\frac{1}{2}$ in.	2.50
3 ft. 0 in. x 7	ft. 0 in. $x 1\frac{1}{2}$ in.	2.80
Window Frames		
$2\frac{1}{2}$ ft. x $4\frac{1}{2}$ ft.		\$1.10
3 ft. x 5 ft.		1.20

## **STAIRS**

The trade of stair-building, while a part of the general work of joinery, is usually taken up as a separate trade and is done by men who do nothing else. For this reason it is better, if possible, to have the stairs figured and built by a regular stair-builder, who will have the special tools, moulds, and stock necessary for this branch of carpenter work.

There are usually in every house, two sets of stairs, one in the front part of the house and one in the back part. Sometimes the stairs are so arranged as to land together in the second story, but divide somewhere in their height upon a common landing, one part, the more ample and elaborate, running from the front hall,




Fig. 14. Combination Staircase.

and the other from the back hall or kitchen. This is called a combination staircase and is often an economical solution of the problem of front and back stairs. See Fig. 14.

When two separate staircases are put in, each will have a distinct character, and it is this condition that we shall consider.

Front Stairs. The front stairs of ordinary width and elaboration, say from 3 ft. to 4 ft. wide with turned balusters and moulded rails and posts, in white wood or North Carolina pine, may be approximated

at \$3.50 to \$4.50 per step, complete. This is on the basis \$1.50 per step for labor, the remainder for the stock. Panelling in connection with the stairs should be figured at \$.40 to \$.50 per sq. ft. of which one-half will be labor and the other half the stock. For ash add 50 per cent, for oak 75 per cent.

Winding steps will cost about double the price of straight steps for material, but the labor will be increased only about 50 per cent. This price will allow of hard pine treads and plain moulded rail with  $1\frac{1}{2}$  in. turned balusters, two to a tread.

No more definite data can be given as to front stairs, as there is such a wide variation in design and finish, and such a wide range in selection of posts, rails, and balusters.

In general a good moulded and panelled newel may be had for \$5.00 to \$8.00, landing posts \$3.00 to \$4.00, rail 15 to 18 cents

per lineal foot, balusters 9 to 12 cents each. Balusters turned in colonial pattern with an upper shaft, a square, and an urn-shaped turning at the base, will cost, turned to detail, about 18 cents; if twisted, add 30 cents. See Fig. 15.

These prices are for open string stairs, if brackets are used on the outside stringer, it will add 12 to 15 cents per step.

Back Stairs. Common box stairs, for general use in the back and attic portions of a house, will cost about \$1.60 per step, this includes 85 cents for stock and 75 cents for labor. Winders will be used more frequently here than in front stairs and will cost about double the price of a straight step. Open cellar stairs of plank with no risers will cost about 65 cents per step, giving 20 cents for labor and 45 cents for stock.




Fig. 15. Balusters in Colonial Pattern.

Summary. From the foregoing it will be found that a flight of front stairs in white wood will cost, at the average run of 16 steps, about \$64.00; and the same in ash \$96.00; in oak \$112.00. This is a fair price for good plain work and will give a satisfactory result.

The back stairs at 15 steps would cost \$24.00 and the cellar stairs \$7.80. Under conditions where much of the handrailing could be done away with, the prices could be reduced considerably.

#### DAY'S WORK

A carpenter in one day can do any one of the following items:

400 running feet of plaster grounds

40 pairs of bridging

1 window, complete, frame, sash, and fittings

1 door, setting frame, hanging, casing, and fitting with hardware Casing windows, 4 per day
Hanging and fitting blinds, 10 pairs per day
Hanging and fitting doors, 5 per day
Casing doors, 5 per day

Cost of labor per square of 100 feet:	
Framing of floors, per square	\$1.50
Framing of walls	1.50
Framing of plain roofs	1.50
Framing of hip and valley roofs	2.00
Heavy framing	1.20
Boarding walls	.75
Boarding walls with matched boards	1.00
Boarding walls diagonally	1.00
Boarding roofs	1.00
Laying rough floor	.75
Laying rough floor diagonally	1.00
Bridging floors	.50
Furring brick walls 12 in. on centers	1.50
Furring brick walls 16 in. on centers	1.00
Laying spruce upper floor, 6 in. stock	1.50
Laying spruce upper floor, 4 in. stock	2.00
Laying hardwood floors, 2½ in. stock	2.50
Shingling walls and roofs	2.18
Clapboarding walls	2.18
Papering walls under shingle or clapboards	.25
Work by the piece; labor:	
Making window frames	\$1.25
Making door frames	1.00
Door frame with transom	1.50
Setting window frames, each	.30
Setting window frames in brickwork, each	.50
Hanging blinds, per pair	.32
Fitting and hanging sashes per pair	.50
Hanging transoms	.40
Casing windows	.80

Large size windows	\$1.50
Attic and cellar windows	.75
Casing door opening, one side	.32
Casing door opening, both sides	.65
Fitting, hanging, and trimming door	.65
Fitting, hanging, and trimming outside door	1.00
Pair of sliding doors, double	13.00
Work in common closet	1.50

Exterior Finish. The exterior finish of a house will consist, in the main, of the water table at the bottom, the belt midway, and the cornice at the top.

Prices of labor per lineal foot:

Water table, 3 members at 3 cents	\$0.09
-Corner boards	.03
Belt ·	.08
Cornice, 3 to 6 cents each member, or per ft.	.50
Gable finish, lineal foot	.60

Piazzas and Porches. An ordinary piazza will cost, complete, about 75 cents a square foot, making for an 8 ft. piazza a cost of \$6.00 per running foot.

Shingled	piazza	columns	each:
----------	--------	---------	-------

11 ft. studding at $2\frac{1}{4}$ cents	
1 bunch shingles	1.0
Nails	
Labor	4.0

# Square cased columns 8 in. x 8 in. will cost, each:

Stock	\$1.50
Labor	1.50
Erecting	.50
	\$3.50

A simple balustrade of straight square balusters 1½ per running foot:	in. will cost
Top rail 3 in x 4 in.	\$0.12
Bottom rail 2 ft. x 4 in.	.08
Balusters, four to a foot	.12
Labor	.32
	\$0.64
Piazza ceiling per square:	
Sheathing	\$4.00
Waste	1.25
Furring .	1.50
Nails	.25
Labor	1.50
	\$8.50
Piazza Finish:	
Stock pattern, 5 in. turned columns 8 ft. long	\$ 2.00
Stock pattern, 6 in. turned columns 8 ft. long	2.75
Stock pattern, 8 in. Colonial columns 9 ft. long	3.50
Stock pattern, 10 in. Colonial columns 9 ft. long	5.50
8 in. Doric Column from detail 9 ft. long	6.50
10 in. Doric Column from detail 9 ft. long	8.50
10 in. Fluted Column from detail 9 ft. long	15.00
Short Posts, 5 in. x 5 in. x 4 ft. 0 in.	1.00
Short Posts, 6 in. x 6 in. x 4 ft. 0 in.	1.50
Piazza balusters $1\frac{3}{4}$ in., 14 in. to 16 in. long, .06 to	.10
Piazza rail $1\frac{3}{4} \times 3\frac{3}{4}$ in. per ft.	.06
Piazza rail $2\frac{1}{4} \times 3\frac{3}{4}$ in. per ft.	.07
Tin roof per square 10.00	to 12.00
Conductors:	
15 ft. pipe at 15 cents	\$2.25
Gooseneck and labor	.65
Putting up	.50
	\$3.40

## **HARDWARE**

The best way to get at the cost of hardware is to get a schedule and price for each job from the dealer. The price of hardware is constantly changing. Prices are given here for a few staple articles of ordinary value.

Nails per cwt.		\$2.50	to	\$4.00
Front door set (bronze metal)		7.00	to	10.00
Vestibule door set		6.00	to	8.00
Inside door set		1.00	to	1.50
Store door set		6.00	to	10.00
Single sliding door set		1.50	to	2.00
Double sliding door		2.00	to	3.00
Double acting floor hinge per pair		3.50	up	
Double acting spring hinge "		2.00	up	
Window fixture, weights, etc.		1.10	up	
Sash fast each	.28	5 to .35		
Transom fixture	.30	to .50		
Cupboard door set		.60		
Folding door bolts		1.25	to	3.00
Flush bolts per pair		1.50		
Butts, small size per pair		.25		
Butts, ordinary size, per pair		.30	to	.40
Double coat and hat hooks, per doz	zen	2.50		
Screws, per gross, bronze		.85		
Single sliding door hanger	2.50	to $3.75$		
Double sliding door hanger	3.50	to 5.50		

#### NAILS

Nails are priced from a base price per hundred weight adopted by the manufacturers, which includes certain sizes of the more common kinds. From this base the different kinds of nails are priced by means of extras, as agreed upon. The present base includes common, fence, and sheathing nails in sizes from 20 penny to 60 penny.

Following is a schedule of all kinds of cut and wire nails in general use and the extra price of each kind per cwt. above the base, which is \$2.50 per cwt., for cut nails and \$2.45 per cwt. for wire nails.

# National List of Extras per cwt. for Cut Nails in Fair Assortment. Adopted Dec. 1, 1896

Common, Fence, and She	eathing	Fine Fi	nishing Extras
Base 20d to 60d	\$2.50*	10d and larg	er \$0.25
*(Variable. July, 1907, \$2.6	65.)	8d and 9d	.35
	Extras	6d and 7d	.45
10d to 16d	\$0.05	4d and 5d	.65
8d and 9d	.10		
6d and 7d	.20	Barrel, Ro	ofing, and Cottage
4d and 5d	.30	$1\frac{1}{2}$ inch	\$0.30
$3\frac{1}{2}d$	.40	$1\frac{3}{8}$ inch	.40
3d	.45	1 <sup>1</sup> / <sub>4</sub> inch	.50
3d fine	.65	1½ inch	.60
2d	.70	1 inch	.70
		7/8 inch	.85
Spikes, all sizes	.10	3 inch	1.00
Casing, Box, and Flo	oor		Clinch
10d and larger	\$0.15	3 in. and lar	
8d and 9d	.25	$2\frac{3}{4}$ and $2\frac{1}{2}$ i	
6d and 7d	.35	$2\frac{1}{4}$ and 2 i	
4d and 5d	.50	$1\frac{3}{4}$ and $1\frac{1}{2}$ i	n75
3d	.70	1¼ in.	.95
2d	1.00	1 in.	1.15
		10 cents	for each $\frac{1}{2}$ keg
Slating			
6d	\$0.40	4d Swedes (	Genuine \$1.30
4d and 5d	.50	4d Swedes C	Common .80
3d	.75		
2d	1.00	Galvanizing	$2\frac{1}{2}$ cts. per lb.
		Tinning	3 cts. per lb.
Size 2d 3d 3	d 4d	5d 6d 7	d 8d 9d 10d
	$\frac{1}{2}$	$1\frac{3}{4}$ 2 2	
1 14 18	, 12	14 2 2	4 22 24 0
Size 12d 20	bl	30d 40d	50d 60d
Length $3\frac{1}{2}$ 4		$\frac{400}{42}$ 5	$\frac{500}{5\frac{1}{2}}$ 6
Length 37		12 0	0

# WIRE NAILS

# Adopted Dec. 1, 1896.

Common, Fence, and	Flooring	Smooth Finishing Nail	s Extras
Base 20d to 60d	\$2.45*	10d and larger	\$0.25
* (Variable. July, 1907, \$2.55	.)	8d and 9d	.35
	Extras	6d and 7d	.45
10d to 16d	\$0.05	4d and 5d	.65
8d and 9d	.10	3d	.85
6d and 7d	.20	2d	1.15
4d and 5d	.30		
$3\frac{1}{2}d$	.40		
3d	.45	Barrel	
3d fine	.50	$\frac{3}{4}$ in.	\$1.00
2d	.70	$\frac{7}{8}$ in.	.85
		1 in.	.70
Barbed Common and	Barbed	$1\frac{1}{8}$ in.	.60
Car Nails		$1\frac{1}{4}$ in.	.50
15c. advance over comm	on	$1\frac{3}{8}$ in.	.40
		$1\frac{1}{2}$ in.	.30
Slating			
2d	\$0.80	Clinch Nails	
3d	.60	2d	\$1.05
4d and 5d	.40	3d	.85
6d	.30	4d and 5d	.65
		6d and 7d	.55
		8d and 9d	.45
Casing and Smooth I		10d	
10d and larger	\$0.15	12d and 16d	.35
8d and 9d	.25	20d	
6d and 7d	.35		
4d and 5d	.50	Wire Spikes	
3d	.70	All sizes	\$0.10
2d	1.00		
Barbed box, 15 cts. adva	nce over s	smooth	

# MISCELLANEOUS DATA

Broken stone filling cu. yd.	\$ 2.50
Cesspool 6 ft. diam. and 8 ft. deep, 8 in. brick	60.00
Blind drains per lineal ft.	.12

Earthen drains 4 in. diam. per foot	\$ .20
Arch brick laid in wall per M.	100.00
Marble mosaic per sq. ft.	.75
Marble threshold, exterior	5.00
Marble base per foot	.50
Granolithic per sq. ft.	.25
Steel beams per lb.	.03
Cast iron per lb.	.02
Copper skylights per sq. ft., heavy 1.75	to 2.50
Plastering 2 coats on wire lath	.65
Wooden balustrade per ft.	1.50
Outside blinds for a house will average per pair	.85
Inside doors, 5 cross panels, pine to paint, average	3.25
Store sash 13/4 in. per lineal foot	.30
Storm sash for house will average	1.55
Outside door frame with transom	3.50
Inside door frames will average	1.10
Same with transoms	1.85
Factory window complete 4 ft. 0 in. × 8 ft. 0 in.	13.00
Framing heavy lumber per M.	12.00
Planing lumber per M.	2.00
Laying plank floors per M.	9.00
Common bricks per M.	9.00
Common bricks laid in wal! per M.	20.00
Concrete foundations per cu. yd.	7.25
Shingling on roof per square	6.54
Slating	11.80
Tar and gravel roof per square	6.00
Tin roofing per square, average	11.00

#### ROOFING

Description. Many kinds of material are used for covering roofs, depending upon the nature of the work, the pitch of the roof, the desired appearance, and the availability of material.

Shingles. The roof covering of an ordinary wooden house is generally of shingles. These are either shaved or sawed, but sawed shingles are generally used. Sawed shingles come in bundles of 250, or four bundles to the thousand. These quantities are based on a width

of 4 in. to each shingle so that if they are wider they will be numerically less and consequently, if narrower, there will be more in number. Common shingles are 16 in. to 18 inches in length.

Measuring. In measuring for shingles the quantities are usually taken by the square; equal to 100 sq. ft., and the number of shingles required will depend upon the lap or exposure which is given to the shingles. On roofs the exposed length is usually  $4\frac{1}{2}$  inches, and on walls 5 or 6 inches is the usual exposure, although in the carrying out of special designs a greater or less exposure may be given.

Quantities. The covering capacity of 1000 shingles at various exposures is as follows:

4 inches to the weather 111 sq. ft. = 900 per square

 $4\frac{1}{2}$  inches to the weather 125 sq. ft. = 800 per square

5 inches to the weather 139 sq. ft. = 720 per square

6 inches to the weather 167 sq. ft. = 600 per square

7 inches to the weather 194 sq. ft. = 514 per square

8 inches to the weather 222 sq. ft. = 450 per square

Cost. Sawed cedar shingles of best quality marked "Extra" will cost from \$4.00 to \$5.00 per thousand, and clear shingles, that is, having the exposed lower third of clear stock, will cost \$3.50 to \$4.00 per thousand, and it will require 5 pounds of 4 penny nails. These will cost 3 cents a pound if plain, or 5 cents, galvanized.




Fig. 16. Slating.

A carpenter in one day of 8 hours will lay 1500 shingles on plain work or 1000 if surface is much cut up. This will cost at \$3.20 per day from \$2.14 to \$3.00.

In estimating shingling an allowance will be necessary for waste; this should be about 5 per cent on plain roofs and 8 to 10 per cent on roofs with many hips, valleys, or dormers.

Slating. Slates are made in different sizes from 6 x 12 up to 16 x 24 and larger sizes for special

work. They are laid with reference to head-cover rather than exposure, that is: the lap of cover of each course by the second above

it, gives the gauge to which slates should be laid, Fig. 16; this lap is usually 3 inches, so that the exposed length of any slate may be found by subtracting this lap from the length of the slate and dividing by 2. This exposure multiplied by the width of the slate gives the exposed area of the slate, and the number of slates in a given area may be found by dividing the area in square inches by the exposed area of the slate.

Example. How many slates will be required per square to cover a roof if 8-in. x 14-in. slates are used?

$$\frac{(14 \text{ in.} - 3 \text{ in.})}{2} = 5\frac{1}{2} \text{ in.}; 8 \text{ in.} \times 5\frac{1}{2} \text{ in.} = 44 \text{ sq. in.}; \frac{14400 \text{ sq. in.}}{44 \text{ sq. in.}} = 327.$$

In measuring a slate roof it is usual to allow an extra width of from 6 inches to a foot, according to localities, on hips, valleys, eaves, and wall cuttings, to allow for the extra work involved.

Extra charge should be made for towers and all varied forms of roof.

Quantities. The number of slates required to cover a square of roofing is given for various sizes in the following table:

6 x	12	533	10 x	20	165
7 x	14	377	11 x	22	138
8 x	16	277	12 x	24	114
9 x	18	214	14 x	28	83

The cost of slating per square is as follows:

Slates	10 in. x 16 in.	\$ 7.50
Labor 1 day, slater		3.50
Nails		.15
Roofing paper		.50
Labor on paper		.15
		\$11.80
Tin roof per sq. ft., avera	age	\$0.11
Gutters per ft., galv. iron		.90
Galv. iron conductors per	ft., put up	.18 to .25
Copper roof, plain per sq	uare	40.00
Copper roof, with battens	s per square	50.00
Gravel roofing, 5-ply per	square	6.00
Zinc flashing, 1½ cents pe	er inch of widt	h, per foot.

Tiles. Where a special feature is to be made of the roof, tiles are often used but these are found in such a variety of shapes, sizes, and prices, that a roof of this sort should always be given to a roofer to estimate.

Metal Roofs. Copper or tin is generally used for roofs where a metal covering is desired. Copper roofs, if steep enough to show as a feature of the building, are usually laid with ribs over battens. This makes a handsome and durable roof the cost being not greatly increased.

Copper roofing will cost from \$35.00 to \$40.00 per square. Flashings around skylights and balustrades, 30 to 50 cents a lineal foot.

For a cheaper metal roof, tin is generally used; this may be used on steep or flat roofs. Tin for roofing should be painted on the under side and carefully soldered on the top.

Tin roofing will cost from \$10.00 to \$12.00 a square.

Composition Roofs. For flat roofs, a composition of tar and paper in layers finished with a protective coat of gravel, is often used; the cost of this depends upon the number of layers of paper and "moppings" of tar required, but a 5-ply roof will give good service and will cost about \$6.00 a square.

Gutters and Conductors. Gutters and conductors are both made of wood or metal, metal being preferred in all cases. For metal gutters copper and galvanized iron are used.

Copper gutters will cost about \$1.25 a lineal foot.

Copper conductors

.50 to .75 a foot

Goosenecks

5.00 to 10.00 each

Moulded conductor heads 4.00 to 10.00 each

Straps

1.00 each

Galvanized iron gutters will cost about 90 cents a lineal foot, and conductors, 18 to 25 cents a foot according to size.

## PLASTERING

Plastering is measured by the square yard and is usually done in 2-coat or 3-coat work. In taking off plastering it is customary to deduct only one-half of the area of openings to allow for the extra work of plastering to the grounds.

In some localities no openings are deducted unless more than 7 yards in area, but in close figuring this is not generally followed.

Narrow strips, such as chimney breasts, if less than a foot wide, are generally called a foot. Round corners, beads, and arrises must be taken separately by the lineal foot.

Raking surfaces require additional work and should be taken at about one-half more than plain work. Circular or elliptical work should be charged at two prices and domes, groins, and intersecting soffits, at three prices. Cornices are taken by the square foot of girth with enrichments charged separately by the lineal foot.

Lathing. Lathing is generally included in the plasterer's price although put up by a different set of men. Lathing is estimated by the square yard or by the thousand laths, the price being \$2.75 to \$3.25 a thousand.

Labor. Two plasterers requiring one helper will do from 40 to 50 square yards of three-coat plastering, or 60 to 70 square yards of two-coat work, in a day of 8 hours, and 1,200 to 1,500 laths makes a day's work for one lather. 100 cq. yds. of lath and plaster will cost about as follows, for two-coat work:

1,500 laths at \$4.75 per M	\$ 7.12
10 lbs. 3d. nails at \$3.20 per cwt.	.32
Labor on 1aths	4.50
10 bushels lime at .48 per bu.	4.80
6 lbs. hair at .04	.24
1 load sand	1.80
Plasterer 3 days at \$5.00	15.00
Helper $1\frac{1}{2}$ days at \$3.00	4.50
Cartage	1.00
	\$39.28

Cost of a square yard of two-coat work,  $$39.28 \div 100 = 39$  to 40 cents.

This is a price which is on the increase and, while plastering is done in the country towns as low as 35 cents per yard it will not be safe to use this price any length of time.

For three-coat work we may take the following	ing schedule:
Laths and putting on, as above	\$11.94
13 bush. lime at .48	6.24
8 lbs. hair at .04	.32
$1\frac{1}{2}$ loads sand at \$1.80	2.70
1 bbl. plaster Paris	1.70
Plasterer 4 days at \$5.00	20.00
Helper 2 days at \$3.00	6.00
Cartage	1.00
	\$49.90

Cost of a sq. yd. of three-coat work, \$49.90 ÷ 100 = 50 cents.

Rules. In some portions of the country a set of rules has been adopted governing the valuing of plasterer's work which are in the main as follows:

"First. Measure on all walls and ceilings the surface actually plastered, without deducting any grounds or any openings of less extent than seven superficial yards.

Second. Returns of chimney-breasts, pilasters, and all strips of plastering less than twelve inches in width, measure as twelve inches wide; and where the plastering is finished down to the base, surbase, or wainscoating, add six inches to height of walls.

Third. In closets, add one-half to the measurement. Raking ceilings and soffits of stairs, add one-half to the measurement; circular or elliptical work, charge two prices; domes or groined ceilings, three prices.

Fourth. For each twelve feet of interior work done farther from the ground than the first twelve feet, add five per cent; for outside work, add one per cent for each foot that the work is done above the first twelve feet."

Stucco-work is generally governed by the following rules; viz., "Mouldings less than one foot girt are rated as one foot, over one foot, to be taken superficial. When work requires two moulds to run same cornice, add one-fifth. For each internal angle or mitre, add one foot to length of cornice, and, for each external angle, add two feet. All small sections of cornice less than twelve inches long measure as twelve inches. For raking cornices, add one-half; circular or elliptical work double price; domes and groins, three prices.

For enrichments of all kinds a special price must be charged. The higher the work is above ground, the higher the charge must be; add to it at the rate of five per cent for every twelve feet above the first twelve feet."

## PAINTING

Painting is estimated by the yard, doors and windows being taken solid to make up for the extra labor of cutting in the sashes and mouldings.

Railings, fences, grilles, and similar surfaces are taken solid.

A painter in one day will cover 100 yds. of outside work one priming coat, or 80 yds. of the second coat. Ten pair of blinds will make a day's work.

On first coat, one pound of paint will cover about 4 sq. yds. and 6 sq. yds. on the subsequent coats. One pound of putty for stopping will cover 20 yds.

Shingle stains require a gallon for every 500 shingles if dipped two-thirds in, and for a brush coat after laying, a gallon will cover about 200 feet of surface, or 1500 shingles.

1 gallon of priming color	will cover 50 yards
1 gallon of zinc white	will cover 50 yards
1 gallon of white paint	will cover 44 yards
1 gallon of black paint	will cover 50 yards
1 gallon of stone color	will cover 44 yards
1 gallon of yellow paint	will cover 44 yards
1 gallon of green paint	will cover 45 yards
1 gallon of emerald green	will cover 25 yards
1 gallon of bronze green	will cover 75 yards

The following table gives the comparative covering of paints by weight on various surfaces.

# COVERING OR SPREADING POWER OF TYPICAL PAINTS\* ON WOOD

	FIRST COAT	SECOND COAT
Rediead	112	252
White lead	221	324

<sup>\*</sup>The figures represent square feet covered by 100 lbs. of paint of the usual consistency, applied evenly with a brush.

F	IRST COAT	SECOND COAT
Oxide of zinc	378	453
Red oxide	453	540
Raw linseed oil	756	872
Boiled linseed oil	412	540
ON METAL		
Red lead	477	
White lead	648	
Oxide of zinc	1134	
Red oxide	870	
Raw linseed oil	1417	
Boiled linseed oil	1296	
ON PLASTER		
Red lead	324	
White lead (on sized wall)	362	
Oxide of zinc	594	
Raw linseed oil (unsized wall)	55	99

Cost. The cost of painting varies under different conditions but in general the following table will be found an average price:

# INSIDE WORK

1 coat per sq. yd.	\$0.12	
2 coats per sq. yd.	.20	
3 coats per sq. yd.	. 25	
1 coat shellac per sq. yd.	.10	
이 없는데 있는데 사람들이 그리고 있다면 하면 하는데 나는데 하는데 하는데 하는데 하는데 하는데 하는데 되었다.	.10	
1 coat size and 2 coats paint	.20	
1 coat size and 3 coats paint stipple	.30	
INSIDE FINISH		
1 coat liquid filler, 1 coat varnish	\$0.20	
1 coat "filler, 2 coats varnish	.25	
1 coat "filler, 3 coats varnish	.30	
1 coat paste filler, 1 coat varnish	.25	
1 coat "filler, 2 coats varnish	.30	
1 coat " filler, 3 coats varnish	.35	

Tinting walls in distemper will cost 15 cents per sq. yd. for small amounts and 10 cents per sq. yd. for 50 yds. or more. Finishing hard wood floors with filler, shellac, and 2 coats of varnish or wax finish will cost 30 cents per sq. yd.

#### OUTSIDE PAINTING

1 coat new work per sq. yard	\$0.10
2 coats new work per sq. yard	.18
3 coats new work per sq. yard	.25

#### SANDING

2 coats paint,	1 coat sand per sq. yd.	\$0.28
3 coats paint,	1 coat sand per sq. yd.	.35
3 coats paint,	2 coats sand per sq. yd.	.50

Painting on brick will cost 12 cents per yard for the first coat, but subsequent coats will cost no more than on wood. Tin roofs can be painted one coat for 5 cents a yard.

1000 shingles dipped two-thirds of their length will cost \$3.00 and a brush coat in addition costs 50 cents. Blinds are rated at \$1.50 per pair for an average size.

#### HEATING

The heating of a building is generally made the subject of a special contract.

The three usual methods for house heating are, the Hot Air Furnace, the Hot Water Boiler, or the Steam Boiler. Sometimes a combination system of hot air and steam, or hot air and hot water is used.

Estimates of the cost of heating should be obtained from contractors who follow this particular branch of construction.

In general, for an ordinary class of building such as residences, apartments, stores, etc., the heating will range according to the system used, from 6% to 12% of the cost of the building, as follows:

Hot air furnace	6 to 7 per cent.
Steam	8 to 10 per cent.
Hot water	10 to 12 per cent.

These figures are approximate and the only reliable way to obtain the actual cost is by taking off the items and figuring each job by itself.

Quantities. The hot air heating of an ordinary house can be approximated closely by the builder on the basis of cubic contents to be heated; and the area of piping and capacity of the furnace can be approximated by means of the following general-rules:

To determine the size of pipe for any room, find the cubic contents of the room in cubic feet and divide this by 25 for rooms on the first floor, and by 35 for rooms on the second and third floors.

Make the cold air box at least  $\frac{3}{4}$  of the combined area of pipes, none of which should be smaller than 7 inches in diameter.

Example. For a small house of seven rooms the quantities may be as follows:

## FIRST FLOOR

Parlor	$12 \times 15 \times 9$ ft. high 1624 cu. ft. divided by $25 = 65$
	sq. in. or 9 in. pipe

Hall  $8 \times 20 \times 9$  ft. high 1440 cu. ft. divided by 25 = 58 sq. in. or 9 in. pipe

Add 40% for second story hall space making 81 sq. in. = 10 in. pipe

Dining Room 14 x 15 x 9 ft. high 1890 cu. ft. divided by 25 = 76 sq. in. or 10 in. pipe

## SECOND FLOOR

Chamber	$13 \times 15 \times 8^{\frac{1}{2}} =$	$1658$ cu. ft. $\div~35$	= 48 sq. in. or 8 in. pipe
Chamber	$11 \times 12 \times 8\frac{1}{2} =$	$1122$ cu. ft. $\div~35$	= 32 sq. in. or 7 in. pipe
Chamber	$14 \times 16 \times 8\frac{1}{2} =$	1904 cu. ft. ÷ 35	= 55 sq. in. or 8 in. pipe
Bath Room	$8 \times 10 \times 8\frac{1}{2} =$	680 cu. ft. ÷ 35	= 20 sq. in. or 7 in. pipe

# Total pipe area:

2 – 10 in. pipes 78 sq. in. each	156 sq. in.
1 - 9 in. pipe 64 sq. in.	64 sq. in.
2 - 8 in. pipes 50 sq. in.	100 sq. in.
2 - 7 in. pipes 38 sq. in.	76 sq. in.
Total pipe area	396

From this scale we can determine the size of the furnace and the cost of piping. A furnace to carry say 400 to 500 sq. feet of pipe area would cost, set in place, from \$100 to \$125. The labor on pipes, registers, and furnace \$20 to \$24.

The cost of piping will depend on the distances to run but the material can be estimated as follows:

Round tin pipes will cost; from A. A. charcoal plates, as follows:

SIZE OF PIPE					10"						100	
Per Foot. Hot Air Damper Furnace Collars. Tin Elbows	.12	.12	$.12 \\ .10$	$.15 \\ .12$	.15	$.15 \\ .14$	.18	.18	.18	$.20 \\ .20$	$.20 \\ .20$	.25

## \* REGISTERS

Size						10x14				
Black Register	.50	.52	.52	.58	.64	1.08	1.37	1.70	2.74	3.75
Slate Stone	.38	.42	.44	.50	.63	.70	.93	1.00	1.50	2.35
Register Box	.14	.16	.17	.20	.23	.27	.33	.35	.38	.50
Netting										
Totals	1.07	1.15	1.19	1.34	1.57	2.12	2.71	3.13	4.72	6.72

\* July, 1906 .- Add one-third.

Galvanized smoke pipe will cost 9c per lb. and will weigh perlineal foot as follows:

Size No.	4"	5"	6"	7"	8"	- 9"	10"	11"	12"	13"	14"
22	13	21/8	25	3	33	31	41	41/2	5	51	53
24	11	15/8	$1\frac{7}{8}$	21/8	$2\frac{1}{2}$	$2\frac{3}{4}$	3	$3\frac{3}{8}$	$3\frac{5}{8}$	37	41

#### GALVANIZED ELBOWS

Size	4"	41/2"	5"	5½"	6"	7"	8"
Pound	1	11	11	13	21	23	31
Cost	.18	.20	.23	.25	.28	.32	.35

## Tin, per Sheet

DC	12½ x 17	.05
IX	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	.07
IXX	14 x 20	.08
IX IX	20 x 23 20 x 26	.12
IX	20 x 29½	.16
IX	$20 \times 32\frac{1}{2}$	.17

## Miscellaneous Data

\$0.05 .04

Galvanized	sheet iron	per lb.	
Common sl	neet iron	per lb.	

Zinc per lb.	\$0.10
Wrought iron per lb.	.04
Galvanized piping per lb.	.09
Galvanized cold air box per lb.	.09
Galvanized furnace shields per sq. ft.	.08
Register box netting per sq. ft.	.05
Asbestos paper at 1½ lbs. per sq. yd.	.05

Figure cold air supply  $\frac{3}{4}$  combined area of piping.

Register grilles take up  $\frac{1}{3}$  of area of register.

Locate registers nearest convenient point to furnace, inside part of room preferred. Locate furnace so that all pipes will be as nearly equal in length as possible.

Estimate pipes by lineal foot, but elbows and dampers separately, also registers with boxes and borders.

Allow from \$1.00 to \$1.25 for flange connection of cold air box to furnace casing.

Cover all risers with asbestos paper in partitions.

## HOT WATER AND STEAM HEATING

In estimating for heating with hot water, all pipes and fittings must be taken off and listed, all standard radiators priced by the square foot of radiation, and special radiators listed separately, also tanks, valves, hangers, etc.

Radiators are listed in the trade catalogues, together with the number of square feet in each section.

These prices are subject to varying discounts which can be obtained of the manufacturers.

Radiation. The amount of radiation necessary for each room depends upon so many varying conditions that all rules are in a way approximate.

Certain formulae may be used, which will give good results in ordinary cases, but just what allowances are necessary must be determined by the heating engineer.

The same is true of making the estimates of hot water or steam and the contractor should in all cases have the job figured by an expert.

In ordinary cases the amount of radiation may be determined

from the cubic contents of the rooms to be heated by the following tables which give the proportions of one square foot of radiating surface to the cubic contents of the various rooms in cubic feet.

## STEAM

One Square Foot of Radiation Will Heat	DWELLINGS, CUBIC FEET	HALLS, STORES, ETC. CUBIC FEET	CHURCHES AND AUDITORIUMS, CUBIC FEET
By direct radiation— On first floor On upper floors	35 to 60 50 to 80	75 to 100	125 to 200
By indirect radiation— On first floor On upper floors	25 to 40 40 to 50	50 to 70	80 to 135

## HOT WATER

One Square Foot of Radiation Will Heat	DWELLINGS, CUBIC FEET	HALLS, STORES, ETC. CUBIC FEET	CHURCHES AND AUDITORIUMS, CUBIC FEET
By direct radiation— On first floor. On upper floors.	15 to 25 25 to 40	30 to 45	50 to 85
By indirect radiation— On first floor On upper floors	17 to 40 25 to 35	45 to 65	80 to 125

Having determined the amount of radiation, piping, and fittings, the labor may be obtained by adding about 20 per cent to the cost of materials.

### **PLUMBING**

So wide a range is possible in the selection and price of plumbing fixtures that no very useful data can be given for a complete installation.

For instance, in one house the price of a single bathroom, fitted up to meet the fancies and purse of the owner, may cost more than the whole plumbing outfit of his more modest neighbor.

Nevertheless, it is a fact that the plumbing of a house is a poor place to practice economy, as no part of the construction of a building needs more careful attention in execution or in selection.

In general, a good job of plumbing will cost about 10 per cent of the cost of the building, and of this outlay about 30 per cent will represent the labor.

In taking off plumbing the contractor should begin at the sewer

or cesspool, if the drains are included, or, if not, at the outer end of the soil pipe, and take off carefully every pipe with its fittings, which should be itemized carefully as this data will be useful in getting at the amount of caulking, fitting, etc.

Soil Pipes. Soil pipes should be estimated by the lineal foot, allowing in each joint  $\frac{3}{4}$  of a pound of lead for every inch in diameter of the pipe.

List prices of pipe and fittings can be obtained from the dealers, which are subject to discount; these vary from time to time, but the present discounts will be found to bring the prices of the more common materials about as follows:

#### DRAINAGE

4-in. extra heavy soil pipe per ft.	\$ .30
3-in. extra heavy soil pipe per ft.	.22
2-in. extra heavy soil pipe per ft.	$.15\frac{1}{2}$
For fittings add 35 per cent to the cost of pipe.	
4-in. running trap	2.00
4-in. brass ferrule cleanout	.50
4-in. lead bend	1.50
4-in. brass ferrule	.50
2-in. brass ferrule	.20
Solder per lb.	.22
WATER SUPPLY	
40 gal. galvanized boiler and stand	\$15.00
1-in. brass pipe per ft.	.60
1-in. galvanized pipe per ft.	.09
<sup>3</sup> / <sub>4</sub> -in. galvanized pipe per ft.	.06
½-in. galvanized pipe per ft.	.05
1-in. stop and waste cock	1.50
<sup>3</sup> / <sub>4</sub> -in. stop and waste cock	.90
½-in. stop and waste cock	.80
Sill cock	1.00
For fittings, add 30 per cent to cost of pipes.	

### WATER

1	cu. ft	t.	7.48 gallons
1	cu. f	t.	29.92 quarts

1 cu. ft., 62.321 lbs.	1004 oz.
1 cu. yd.	1692 lbs.
1 gal., 231 cu. in.	$8\frac{1}{3}$ lbs.
1-foot cylinder	49.1 lbs.
1-inch cylinder	.028 lbs.

Pressure per sq. in. = depth in feet x 433.

Each 27.72 inches of depth gives a pressure of 1 lb. to a square inch.

A barrel  $31\frac{1}{2}$  gal.

Contents in cu. ft.  $\times 2375 = \text{barrels}$ .

Head of water = pressure in lbs, per sq. in. x 2.31.

Number of gallons in a foot of pipe = Diam. in. inches  $2 \times .04$ .

Supply for one person is 15 gallons a day.

Actual use 6 gallons to 12 gallons.

Water 34 feet high has a pressure of 15 lbs. per sq. in. equal to atmosphere.

# CAPACITY OF CISTERNS In Gallons, for Each Foot in Depth

DIAMETER IN FEET	GALLONS	DIAMETER IN FEET	GALLONS
2.	23.5	9.	475.87
2.5	36.7	9.5	553.67
3.	52.9	10.	587.5
3.5	71.96	11.	710.9
4.	94.02	12.	846.4
4.5	119.	13.	992.9
5.	146.8	14.	1,151.5
5.5	177.7	15.	1,321.9
6.	211.6	20.	2,350.0
6.5	248.22	25.	3,570.7
7.	287.84	30.	5,287.7
7.5	330.48	35.	7,189.
8.	376.	40.	9,367.2
8.5	424.44	45.	11,893.2

The American Standard gallon contains 231 cubic inches, or 8½ pounds of pure water. A cubic foot contains 62.3 pounds of water, or 7.48 gallons. Pressure per square inch is equal to the depth or head in feet multiplied by .433. Each 27.72 inches of depth gives a pressure of one pound to the square inch.


For tanks that taper, take diameter  $\frac{4}{10}$  from large end.

#### **FIXTURES**

3-ft. soapstone sink complete \$30.00 to \$40.00 14-in. x 17-in. lavatory with marble slab and back piece fitted complete \$35.00 to \$50.00









HOUSE AT WASHINGTON, ILL. Herbert Edmund Hewitt, Architect, Peoria, Ill.

Walls of Cement on Metal Lath. Roofs Covered with Shingles Stained Green. All Outside Woodwork Stained Dark Brown. No Paint on Outside except on Sash.






# SECOND TOOR RAN HOUSE AT WASHINGTON, ILL.

Herbert Edmund Hewitt, Architect, Peoria, Ill.

Built in 1904. Cost, about \$4,500. House was Built for a Summer House, but Constructed the Same as if for All Year-Round Use, and Provided with Heating Plant.



\$25.00 to \$40.00

Bath tub only	\$25.00 to	\$35.00
Soapstone laundry trays complete		
One part	\$15.00 to	\$18.00
Two parts	\$30.00 to	\$35.00
Three parts	\$45.00 to	\$60.00

5-ft. 6-in, enamelled iron bath complete \$60.00 to \$100.00

List prices of fittings may be obtained from all dealers, subject to large discounts, which should be considered frequently as they are constantly changing.

**Labor.** Having made a complete list of pipe, fittings, and fixtures, the labor of construction of an ordinary job of plumbing will run from 20 to 40 per cent of the cost of materials.

#### GAS FITTING

As in plumbing so in gas fitting, the wide range of selection and cost in fixtures, makes it impossible to give satisfactory data in regard to cost.

The piping only, of an ordinary house will cost from \$1.75 to \$2.00 an outlet, and the whole outfit should cost from 3 to 5 per cent of the cost of the house.

Pipes of usual size cost as follows:

Enamelled iron lavatory complete

<sup>3</sup> / <sub>8</sub> -in. gas pipe per foot	\$0.03
$\frac{1}{2}$ -in. gas pipe per foot	.04
$\frac{3}{4}$ -in. gas pipe per foot	.05
$1\frac{1}{2}$ -in. main	.08

Fittings 25 per cent of cost of pipe.

## ELECTRIC WORK

The original contract for a house usually provides for the wiring for electric lighting and bells, but fixtures are generally left to be provided for by a later agreement, as there is such a great latitude in selection and cost.

For electric light wiring one of two systems is usually employed: the conduit system, where the wires are all run in pipes or conduits, and the knob and tube system, where the wires are run in the clear space between timbers, secured to porcelain knobs, or passing through short tubes of the same material.

In general, the rough wiring of a house may be reckoned at \$4.00 per outlet for conduit work, and \$2.00 per outlet for knob and tube work.

This is for every time the wires are brought to the surface, whether for switches, cutouts, or fixtures. Another way is to allow \$1.50 for each lamp or switch.

Switches. Various kinds of switches are used, the two principal kinds being the push button, and the rotary switch.

These vary in price according to make and finish.

A good rotary switch can be had at from 90 cents to \$1.00.

Push button switches from \$1.00 to \$1.10.

Snap switches from 30 to 40 cents.

Wires are sold in coils which are marked with the gauge and manufacturer, and should bear the label of inspection acceptable to the local Insurance board.

The cost of wire will vary with the gauge and the insulation but for usual house work should cost, for No. 14 wire, 2 cents a foot.


It is well to remember that, in electric wiring, the larger the house, the more per outlet the wiring will cost. This seems contrary to expectation but is occasioned by the smaller percentage of lights to length of wire.

Bells. The number of call bells in a dwelling will vary according to the plan and choice of the owner.

For an ordinary house the number would range from six to ten, and the cost should be from \$18.00 to \$25.00 or about \$3.00 per bell.







HOUSE AT FRAMINGHAM, MASS., AS REMODELED FOR C. LA VERNE BUTLER, ESQ.

Frank Chouteau Brown, Architect, Boston, Mass.

Alterations on this Plaster House Completed in the Spring of 1906 at a Cost of \$8,000. Taking into Consideration the Changes Made in the House and the Work Put in on Repairing and Raising the Roof, etc., an Entirely New House of this Size Could be Built for Nearly this Sum—Certainly within \$9,000.

# **ESTIMATING**

### PART II

The taking-off of quantities and making-up of an actual estimate, is the end toward which our efforts are now directed. This is done, as has been said, in a number of ways, no two persons arriving at the same conclusion or following exactly the same methods. To give the student a practical idea of howestimates are made, we shall now demonstrate the method of procedure in an actual instance. For this purpose, we shall take the case of the wooden Colonial residence of which the plans and working drawings, and the method of making these, are fully described in the course on "Architectural Drawing," and of which the details are also described to a certain extent in the chapters on "Building Superintendence;" and shall proceed at once to take off the quantities and make up an estimate of cost.

Method. The usual method followed is to take off the quantities in the order in which they occur in the specification or in the operation of building, beginning with the Excavation and ending with the Painting.

Two methods of procedure are open to the Contractor, which he may avail himself of according to his experience or confidence. He may take off simply his own particular branch of the work, relying on each sub-contractor to give him a price for the detailed portions of the work; or, if he is a general contractor, he may, with the requisite knowledge of general building operations, take off all the quantities, pricing them according to his knowledge, and may submit his proposition on the basis of his own figures. The latter method requires great experience, and is followed generally by large contractors, who have in their employ men whose business is mainly to take off quantities and make up estimates.

The following estimate has been carefully made up on the basis of the data given in Part I as to prices of materials and labor. In actual practice, details of more or less importance will vary in different localities and among different contractors; but the example here given illustrates the process fully.




Fig. 1.

Fig. 2

# ESTIMATE

OF

# RESIDENCE AT RIDGEDALE, MO. FOR GEORGE A. JONES, ESQ.

Staking-out and setting batter-boards	\$15.00
Water supply during construction	10.00
	\$25.00

### **EXCAVATION**

Note.—Excavation is priced by the cubic yard; and in this regard, the distance to which the excavated material must be carted will be an important consideration. In the present case, the material is to be carried only a short distance, so that no unusual conditions will have to be considered.

As before mentioned, it is usually well to dig a cellar at least a foot larger all around than the sill line, so that plenty of room may be afforded to the mason to plaster the outside of the wall. This should be done without regard to the specifications. As this extra excavation lies entirely outside the line of the house, it may be well to take it off separately, remembering that it will extend down into the trench below the wall, making about 8 feet of height.

cu. ft.




Fig. 3

Brought forward 11,784 cu. ft.
Miscellaneous Quantities—
Piers
2 ft. 0 in. $\times$ 2 ft. 0 in. $\times$ 3 ft. 6 in. $\times$ 12 168
Trench
185 ft. 0 in. $\times$ 1 ft. 8 in. $\times$ 1 ft. 0 in 308
Area
14 ft. 0 in. $\times$ 2 ft. 8 in. $\times$ 3 ft. 6 in 129
Drains
123 ft. 0 in. $\times$ 3 ft. 6 in. $\times$ 1 ft. 6 in 645
Cesspools
$5 \text{ ft. 6 in.} \times 5 \text{ ft. 6 in.} \times 8 \text{ ft. 0 in.} \dots 242$
10 ft. 0 in. $\times$ 19 ft. 0 in. $\times$ 8 ft. 0 in 800
Dry Wells
$6 \times 2$ ft. 0 in. $\times 2$ ft. 0 in. $\times 5$ ft. 0 in. 120
Total, 14,196 cu. ft.
Total, 14,196 cu. ft., or 525 cu. yds., at 50 cents \$262.50
STONEWORK
DRY WALLS IN TRENCH— Cu. Ft.
$16 \text{ ft. } 0 \text{ in.} \times 1 \text{ ft. } 8 \text{ in.} \times 1 \text{ ft. } 0 \text{ in.} \dots 27$
16 ft. 0 in. $\times$ 1 ft. 8 in. $\times$ 1 ft. 0 in 27
12 ft. 6 in. $\times$ 1 ft. 8 in. $\times$ 1 ft. 0 in 20.8
$3 \text{ ft. 0 in.} \times 1 \text{ ft. 8 in.} \times 1 \text{ ft. 0 in.} \dots 5$
23 ft. 0 in. $\times$ 1 ft. 8 in. $\times$ 1 ft. 0 in
$16 \text{ ft. } 6 \text{ in.} \times 1 \text{ ft. } 8 \text{ in.} \times 1 \text{ ft. } 0 \text{ in.} \dots 27.5$
$28  \text{ft.}  0  \text{in.}  \times  1  \text{ft.}  8  \text{in.}  \times  1  \text{ft.}  0  \text{in.}  \dots  46$
$28 \text{ ft. 0 in.} \times 1 \text{ ft. 8 in.} \times 1 \text{ ft. 0 in.} \dots 46$
$14 \text{ ft. 6 in.} \times 1 \text{ ft. 8 in.} \times 1 \text{ ft. 0 in.} \dots 24$
$4 \text{ ft. } 6 \text{ in.} \times 1 \text{ ft. } 8 \text{ in.} \times 1 \text{ ft. } 0 \text{ in.} \dots 7.5$
23 ft. 0 in. $\times$ 1 ft. 8 in. $\times$ 1 ft. 0 in. $\ldots$ 38
Total, 306.8 cu. ft.
307 cu. ft. $\div$ 25 = 12 perches of dry wall.
507 cu. II. $-25 = 12$ perches of dry wan.
MORTAR WALLS—
Mortar Walls—
MORTAR WALLS— 16 ft. 0 in. × 6 ft. 7 in. × 1 ft. 8 in
MORTAR WALLS—  16 ft. 0 in. × 6 ft. 7 in. × 1 ft. 8 in




Fig. 4.

	Brought forward	480 cu. ft.
$23  \mathrm{ft.}  0  \mathrm{in.}  \times  8  \mathrm{ft.}  3  \mathrm{in.}$	× 1 ft. 8 in	316
$12  \mathrm{ft.}  0  \mathrm{in.}  \times  6  \mathrm{ft.}  7  \mathrm{in.}$	× 1 ft. 8 in	132
$28  \text{ft.}  0  \text{in.}  \times  8  \text{ft.}  3  \text{in.}$	× 1 ft. 8 in	385
$6  \mathrm{ft.}  0  \mathrm{in.}  \times  6  \mathrm{ft.}  7  \mathrm{in.}$	× 1 ft. 6 in	59
$10  \mathrm{ft.}  0  \mathrm{in.}   imes  6  \mathrm{ft.}  7  \mathrm{in.}$	× 1 ft. 0 in	66
$8  \text{ft. 6 in.} \times 6  \text{ft. 7 in.}$	× 1 ft. 8 in	93
9 ft. 0 in. $\times$ 8 ft. 3 in.	× 1 ft. 8 in	123
$25  \mathrm{ft.}  0  \mathrm{in.}  \times  6  \mathrm{ft.}  7  \mathrm{in.}$	× 1 ft. 8 in	274
$6  \mathrm{ft.}  0  \mathrm{in.}  \times  6  \mathrm{ft.}  7  \mathrm{in.}$	× 1 ft. 8 in	66
$23  \text{ft.}  0  \text{in.}  \times  6  \text{ft.}  7  \text{in.}$	× 1 ft. 8 in	252
Piers—		
$2  \text{ft. 6 in.} \times 5  \text{ft. 6 in.}$		14
$2  \text{ft. 6 in.} \times 5  \text{ft. 6 in.}$		14
$2  \text{ft.}  0  \text{in.} \times 2  \text{ft.}  0  \text{in.}$		4
$12  \text{ft. 0 in.} \times 3  \text{ft. 6 in.}$		84
$12  \text{ft.}  0  \text{in.}  \times  3  \text{ft.}  6  \text{in.}$	$\times$ 2 ft. 0 in	84
Area—		
$14  \text{ft. 0 in.} \times 3  \text{ft. 6 in.}$	$\times$ 1 ft. 6 in	73
	Total,	2,519 cu. ft.
$2,519 \text{ cu. ft } \div 25 = 10$		
	1 perches of mortar	wall.
Underpinning-	1 perches of mortar	wall. Cu. Fr.
Underpinning— $16  \text{ft.}  0  \text{in.}  \times  1  \text{ft.}  8  \text{in.}$	1 perches of mortar ( × 1 ft. 8 in	wall. Cu. Ft. 45
Underpinning—	1 perches of mortar ( × 1 ft. 8 in	wall. Cu. Fr. 45 45
$\begin{array}{c} \text{Underpinning} \\ 16 \text{ ft. 0 in.} \ \times \ 1 \text{ ft. 8 in.} \\ 16 \text{ ft. 0 in.} \ \times \ 1 \text{ ft. 8 in.} \\ 6 \text{ ft. 0 in.} \ \times \ 1 \text{ ft. 8 in.} \end{array}$	1 perches of mortar (	wall. Cu. Ft. 45 45 17
Underpinning— $16 \text{ ft. 0 in.} \times 1 \text{ ft. 8 in.}$ $16 \text{ ft. 0 in.} \times 1 \text{ ft. 8 in.}$ $6 \text{ ft. 0 in.} \times 1 \text{ ft. 8 in.}$ $12 \text{ ft. 0 in.} \times 1 \text{ ft. 8 in.}$	1 perches of mortar ( × 1 ft. 8 in	wall. Cu. Ft. 45 45 17 34
Underpinning—  16 ft. 0 in. × 1 ft. 8 in.  16 ft. 0 in. × 1 ft. 8 in.  6 ft. 0 in. × 1 ft. 8 in.  12 ft. 0 in. × 1 ft. 8 in.  6 ft. 0 in. × 1 ft. 8 in.  6 ft. 0 in. × 1 ft. 8 in.	1 perches of mortar ( × 1 ft. 8 in	wall. Cu. Fr. 45 45 17 34 6
$\begin{array}{c} \text{Underpinning} \\ 16 \text{ ft. 0 in.} \ \times \ 1 \text{ ft. 8 in.} \\ 16 \text{ ft. 0 in.} \ \times \ 1 \text{ ft. 8 in.} \\ 6 \text{ ft. 0 in.} \ \times \ 1 \text{ ft. 8 in.} \\ 12 \text{ ft. 0 in.} \ \times \ 1 \text{ ft. 8 in.} \\ 6 \text{ ft. 0 in.} \ \times \ 1 \text{ ft. 0 in.} \\ 8 \text{ ft. 6 in.} \ \times \ 1 \text{ ft. 8 in.} \end{array}$	1 perches of mortar ( × 1 ft. 8 in	wall. Cu. Ft. 45 45 17 34 6 23
$\begin{array}{c} \text{Underpinning} \\ 16 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 16 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 6 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 12 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 6 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 8 \text{ ft. 6 in.} & \times 1 \text{ ft. 8 in.} \\ 25 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ \end{array}$	1 perches of mortar (  × 1 ft. 8 in	wall. Cu. Fr. 45 45 17 34 6 23 70
$\begin{array}{c} \text{Underpinning} \\ 16 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 16 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 6 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 12 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 6 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 8 \text{ ft. 6 in.} & \times 1 \text{ ft. 8 in.} \\ 25 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 6 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ \end{array}$	1 perches of mortar (  × 1 ft. 8 in.  × 1 ft. 8 in.	wall. Cu. Ft. 45 45 17 34 6 23 70 17
$\begin{array}{c} \text{Underpinning} \\ 16 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 16 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 6 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 12 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 6 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 8 \text{ ft. 6 in.} & \times 1 \text{ ft. 8 in.} \\ 25 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 6 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 23 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 23 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ \end{array}$	1 perches of mortar (  × 1 ft. 8 in	wall. Cu. Ft. 45 45 17 34 6 23 70 17 64
$\begin{array}{c} \text{Underpinning} \\ 16 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 16 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 6 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 12 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 6 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 8 \text{ ft. 6 in.} & \times 1 \text{ ft. 8 in.} \\ 25 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 6 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ \end{array}$	1 perches of mortar (  × 1 ft. 8 in	wall. Cu. Ft. 45 45 17 34 6 . 23 70 . 17 64 42
Underpinning—  16 ft. 0 in. × 1 ft. 8 in.  16 ft. 0 in. × 1 ft. 8 in.  6 ft. 0 in. × 1 ft. 8 in.  12 ft. 0 in. × 1 ft. 8 in.  6 ft. 0 in. × 1 ft. 8 in.  6 ft. 0 in. × 1 ft. 8 in.  8 ft. 6 in. × 1 ft. 8 in.  25 ft. 0 in. × 1 ft. 8 in.  6 ft. 0 in. × 1 ft. 8 in.  23 ft. 0 in. × 1 ft. 8 in.  14 ft. 0 in. × 2 ft. 0 in.	1 perches of mortar (  × 1 ft. 8 in	wall. Cu. Fr. 45 45 17 34 6 . 23 70 . 17 64 42 363 cu. ft.
$\begin{array}{c} \text{Underpinning} \\ 16 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 16 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 6 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 12 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 6 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 8 \text{ ft. 6 in.} & \times 1 \text{ ft. 8 in.} \\ 25 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 6 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 23 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ 23 \text{ ft. 0 in.} & \times 1 \text{ ft. 8 in.} \\ \end{array}$	1 perches of mortar (  × 1 ft. 8 in	wall. Cu. Fr. 45 45 17 34 6 . 23 70 . 17 64 42 363 cu. ft.
Underpinning—  16 ft. 0 in. $\times$ 1 ft. 8 in.  16 ft. 0 in. $\times$ 1 ft. 8 in.  6 ft. 0 in. $\times$ 1 ft. 8 in.  12 ft. 0 in. $\times$ 1 ft. 8 in.  12 ft. 0 in. $\times$ 1 ft. 8 in.  6 ft. 0 in. $\times$ 1 ft. 8 in.  8 ft. 6 in. $\times$ 1 ft. 8 in.  25 ft. 0 in. $\times$ 1 ft. 8 in.  25 ft. 0 in. $\times$ 1 ft. 8 in.  23 ft. 0 in. $\times$ 1 ft. 8 in.  14 ft. 0 in. $\times$ 2 ft. 0 in.  363 cu. ft. $\div$ 25 = 14½  Summary of Stonework—	1 perches of mortar (	wall. Cu. Fr. 45 45 17 34 6 23 70 17 64 42 363 cu. ft. ning.
Underpinning—  16 ft. 0 in. $\times$ 1 ft. 8 in.  16 ft. 0 in. $\times$ 1 ft. 8 in.  6 ft. 0 in. $\times$ 1 ft. 8 in.  12 ft. 0 in. $\times$ 1 ft. 8 in.  12 ft. 0 in. $\times$ 1 ft. 8 in.  6 ft. 0 in. $\times$ 1 ft. 8 in.  8 ft. 6 in. $\times$ 1 ft. 8 in.  25 ft. 0 in. $\times$ 1 ft. 8 in.  25 ft. 0 in. $\times$ 1 ft. 8 in.  23 ft. 0 in. $\times$ 1 ft. 8 in.  14 ft. 0 in. $\times$ 2 ft. 0 in.	1 perches of mortar (	wall. Cu. Fr. 45 45 17 34 6 23 70 17 64 42 363 cu. ft. ning.

Brought forward \$	36.00
101 perches of mortar walls, at \$4.25	429.25
101 perches of mortal wans, at $94.25$ 14½ perches of underpinning, at $$6.50$	
네트 이번 보고 하면서 및 바람이 시민에서 가면서 되었다. [18] 이 사람들은 사람들에 되었다. 이 사람들이 되었다. 이 전에 가는 것이 되었다.	
Total cost of Stonework,	\$559.50
PLASTERING WALLS WITH CEMENT	
$192  \text{ft.}  0  \text{in.} \times 6  \text{ft.}  7  \text{in.} = 1,264  \text{sq. ft.} = 140  \text{sq. yds.},  \text{at $\$.40}$	\$ 56.00
CESSPOOLS	•
Leaching Cesspool—	
23 ft. 6 in. $\times$ 8 ft. 0 in. $\times$ 1 ft. 6 in. = 282 cu. ft. $\div$ 25=	
$11\frac{1}{3}$ perches.	
$11\frac{1}{3}$ perches at \$3.50\$39.65	
Cover	42.15
TIGHT CESSPOOL—	
11 ft. 6 in. $\times$ 8 ft. 0 in. = 92 sq. ft. $\times$ 15 bricks =	
1,380 bricks.	
1,380 bricks at \$20.00 per M \$27.60	
Iron cover	30.60
DRY WELLS	
2 ft. 0 in. $\times$ 2 ft. 0 in. $\times$ 5 ft. 6 in. $\times$ 12 = 264 cu. ft. $\div$ 25 =	
11 perches 11 perches at \$2.50	27 50
11 perches at \$2.50	27.50
DRAINS	
171 ft. at \$.20. \$34.20	
14 bends at \$.30 4 .20	38.40
Total cost of Stonework, Cesspools, and Drains	\$754.15
BRICKWORK	
Note.—Find the number of bricks in a foot of height	in each
chimney or pier, reckoning five courses to the foot of height.	
Cellar—	
$35 \times 8 \dots 280$	
$107\frac{1}{2} \times 8$	
55 × 8	
Carried forward 1,580 k	oricks





Fig. 5.

· RESIDENCE-AT-RIDGEDALE, MO-FOR. GEORGE-A SJONEN - ENQ -Frank. A. Bourne, Architect. Majon. Boilding



FRAMING-OF-FRONT-ELEVATION-

\*Cale of [ ] 1 1 1 1 1 | Jeet\*

Fig. 7,

	Brought forward 1,580 bricks
Veranda Piers—	
$58\frac{1}{2} \times 10$	585
CHIMNEYS—	
$107\frac{1}{2} \times 6 \text{ ft. 6 in.} \dots$	700
$105 \times 11 \text{ ft. } 0 \text{ in} \dots$	
$35 \times 11 \text{ ft. 0 in.} \dots$	
$35 \times 4 \text{ ft. 6 in.} \dots$	
가는 보다 있는 것이 되었다. [1] (1) 가는 바로 보는 사람들이 되었다. 그런	701
$35 \times 19$ ft. 0 in	665
$57\frac{1}{2} \times 4 \text{ ft. 0 in.} \dots$	230
$127\frac{1}{2} \times 11 \text{ ft. 0 in.} \dots$	<u>1, 402</u>
	7,560 bricks
Summary—	
	aid \$ 151.20
3 fireplaces at \$30.00 each	90.00
Flue Linings—	
$26  \text{ft.}, 13  \text{in.} \times 13  \text{in.}, \text{at } \$.35$	
36 ft., 9 in. round, at \$.30	
$68  \text{ft.}, 8\frac{1}{2} \times 13, \text{at } \$.30 \dots$	The state of the s
Total cost of Brick	work and Flue Linings, \$ 281.50
CONCR	ETING
	Sq. Ft.
$23  \text{ft.}  0  \text{in.}  \times  38  \text{ft.}  0  \text{in}$	n 874
$3  \mathrm{ft.}  0  \mathrm{in.}  \times  9  \mathrm{ft.}  6  \mathrm{in}$	$1$ $28\frac{1}{2}$
15 ft. 0 in. × 26 ft. 0 in.	n 390
4 ft. 0 in. × 7 ft. 0 i	n 28
	1,320 sq. ft.
Total, $1,320 \text{ sq. ft.} = 147 \text{ sq. yds.}$ , at	\$88.20
PLASTI	EDING
Note.—Take off square feet one-half of the openings, after red	of plastered surfaces, and deduct
CELLAR—	SQ. FT.
$23  \mathrm{ft.}  0  \mathrm{in.}   imes  38  \mathrm{ft.}  0  \mathrm{in}$	
9 ft. 6 in. $\times$ 3 ft. 0 in	
· ·	Carried forward 902 sq. ft.




Fig. 8.

	Propert forward 002 on ft	
15 ft 6 in	Brought forward 902 sq. ft. × 26 ft. 0 in 403	
30 It. 0 III.	$\times$ 8 ft. 0 in	
Troom Coopy	1,545 sq. 1t.	
FIRST STORY—	× 40 ft. 0 in 1,000	
	× 3 ft. 0 in	
	× 16 ft. 6 in	
	× 9 ft. 0 in 4,410	
490 11. 0 111.	5,863 sq. ft.	
SECOND STORY—	0,000 34. 11.	
DECOND DIONI	Sq. Ft.	
25 ft. 0 in.	× 40 ft. 0 in	
	× 19 ft. 0 in	
520 ft. 0 in.	× 8 ft. 6 in 4,420	
	5,733 sq. ft.	
Total amount of plast	ered surfaces, 13,141 sq. ft.	
Outs-		
32 doors, av	verage 40 sq. ft	
34 windows	s, average 15 sq. ft 510	
	1,790 sq. ft.	
1,790 sq. ft.	$\div 2 = 895 \mathrm{sq.}\mathrm{ft.}$	
13,141 sq. ft. less 895	sq. ft. = 12,246 sq. ft. = 1,361 sq. yds.	
Total cost of Plastering	; 1,361 sq. yds., at \$.40 \$ 544.40	
	CARPENTER WORK	
Frame-		
	Ft. B. M.	
	t., $6 \times 6$ in. sill	
190	$4 \times 6 \text{ in. } \dots 272$	
./4	' 8 × 10 in. girders 494	
200	$4 \times 6$ in. posts 500	
188 " '	' 4 × 6 in. girts 376	
	2,206	
2,206 ft. B. M. at \$38.0	0 per M	
FIRST-STORY FRAME, BRIDGING AND UNDER FLOOR—		
25 ft. 0 in.	× 40 ft. 0 in	
	Carried forward \$ 83.82	






Fig. 9.






Brought forward \$ 83.82
11 ft. 0 in. $\times$ 3 ft. 0 in
26 ft. 0 in. × 16 ft. 6 in 429
$\overline{1,462}$ sq. ft.
1,462 sq. ft. = 14.62 squares, at \$9.35 per square \$ 136.70
UPPER FLOOR—
Hard Pine
$25  \text{ft.}  6  \text{in.} \times 16  \text{ft.}  6  \text{in.} = 421  \text{sq.}  \text{ft.}, \text{at } \$10.50$
per square \$ 44.21
Oak
$25 \text{ ft. } 0 \text{ in.} \times 40 \text{ ft. } 0 \text{ in.} = 1,000 \text{ sq. ft.}$
11 ft. 0 in. $\times$ 3 ft. 0 in. = 33 "
1,033 sq. ft.
1,033 sq. ft. at \$20.00 per square \$ 206.60
Porch Floor—
$6 \text{ ft. } 0 \text{ in.} \times 11 \text{ ft. } 0 \text{ in.} = 66 \text{ sq. ft.}$
$9 \text{ ft. } 0 \text{ in. } \times 5 \text{ ft. } 0 \text{ in, } = 45$ "
PIAZZA FLOOR— $26 \text{ ft. 0 in.} \times 9 \text{ ft. 0 in.} = 234 \text{ "}$
20 ft. 0 in. $\times$ 9 ft. 0 in. = 234 20 ft. 6 in. $\times$ 7 ft. 0 in. = 144 "
201t. 6 III. × 7 It. 6 III. = 144 489 sq. ft.
489 sq. ft. at \$12.35 per square \$ 60.39
Second-Story Frame, Bridging and Strapping Floors—
40 ft. 0 in. × 25 ft. 0 in 1,000 sq. ft.
20 ft. 0 in. × 17 ft. 0 in
1,340 sq. ft.
1,340 sq. ft. at \$18.00 per square \$ 241.20
Third Story—
1,340 sq. ft. at \$10.10 per square \$ 135.34
Roof Frame, Boarding and Shingles-
$30  \mathrm{ft.}  0  \mathrm{in.} \times 16  \mathrm{ft.}  6  \mathrm{in.} \times 2  \mathrm{sides.}$ . $990  \mathrm{sq.}  \mathrm{ft.}$ .
34 ft. 0 in. × 16 ft. 6 in. × 2 sides 1,122 ""
2,112 sq. ft.
2,112 sq. ft. at \$16.67 per square \$ 352.07
FLASHING
Tin Roof, Frame and Boarding—
21 ft. 0 in. × 7 ft. 6 in 157 sq. ft.
Carried forward \$1,300.33



-PLAN-OF-THIRD-FLOOR-&-ROOF-


$Brought\ forward$	@1 200 22
19 ft. 0 in. $\times$ 6 ft. 6 in 124 sq. ft.	\$1,300.33
11 ft. 0 in. × 5 ft. 6 in 60 " "	
14 ft. 0 in. × 9 ft. 6 in	
$\frac{135}{474} \text{ sq. ft.}$	
474 sq. ft. at \$20.92 per square	\$ 99.16
Outside Walls, Studding and Boarding—	
172 ft. 0 in. × 20 ft 0 in 3,440 sq. ft.	
6 ft. 6 in. $\times$ 10 ft. 0 in. $\times$ 2 sides 130 " "	
$3 \text{ ft. 0 in.} \times 9 \text{ ft. 0 in.} \times 2 \text{ sides} \qquad 54 \text{ ""}$	
$\overline{3,624}  \text{sq. ft.}$	
3,624 sq. ft. at \$8.30 per square	\$ 300.79
Inside Studding—	
180 ft. 0 in. × 9 ft. 0 in 1, 620 sq. ft.	
196 ft. 0 in. × 8 ft. 6 in 1, 666 " "	
28 ft. 0 in. × 8 ft. 0 in	
$\overline{3,510}$ sq. ft.	
3,510 sq. ft., at \$4.00 per square	\$ 140.40
CLAPBOARDING—	
$44  \text{ft. 0 in.} \times 19  \text{ft. 0 in.} \times 2  \text{sides. } 1,672  \text{sq. ft.}$	
6 ft. 0 in. × 8 ft. 0 in. × 2 sides. 96 " "	
2 ft. 0 in. $\times$ 9 ft. 0 in. $\times$ 2 sides. 36 " "	
$39  \text{ft.}  0  \text{in.} \times 19  \text{ft.}  0  \text{in.} \times 2  \text{sides.}  1,482  \text{```}$	
$\overline{3,286}$ sq. ft.	
3,286 sq. ft. at \$7.95 per square \$261.23	
Deduct for stock only, 36 windows	
= 54f. sq. ft., at \$4.70 per square 25.38	\$ 235.85
MISCELLANEOUS	
Dormers—	
6, at \$50 each	\$ 300.00
Main Cornice—	
180 ft., at \$1.25 per ft	225.00
Balustrade on Roof—	
96 ft., at \$0.50 per ft \$48.00	
18 posts, at \$1.50 each 27.00	75.00
Carried forward	\$2,676.53

PIAZZA FINISH—	Brought forward \$2,676.53
Cornice—	
102 ft., at \$2.00 per ft	204.00
Columns—	
9 in place, at \$10.00 each	
Corner Pilasters—	
$2\frac{1}{2}$ in place, at \$8.00 each	20.00
Balustrade—	
76 ft., at \$.50 per ft	\$38.00
Small Posts—	
$8\frac{1}{2}$ , at \$1.00 each	12.00 50.00
Outside Steps	25.00
Lattice—	
$55  \text{ft.}  0  \text{in.} \times 1  \text{ft.}  6  \text{in.} = 82\frac{1}{2}  \text{sq}$	ı. ft., at \$.15
per sq. ft	
Porch Ceiling—	
111 sq. ft., at \$10.00 per square.	11.10
BULKHEAD STEPS	
Corner Boards—	
$252  \text{ft.}  0  \text{in.} \times 8  \text{in.} = 168  \text{sq.}  \text{ft.}$	., at \$.30 per sq. ft. 50.40
WATER TABLE—	
$117\frac{1}{2}$ linear ft., at \$.20 per ft	23.50
Windows and Frames—	
Attic—	
4 windows, circular top, at	\$11.20 each \$ 44.80
4 windows, square, at	
Second Story—	
8 windows, 3 ft. 6 in. $\times$ 5 ft. 0 in.	at \$13.33 each \$106.64
7 windows, 2 ft. 6 in. $\times$ 4 ft. 6 in.	
First Story—	
1 window, 2 ft. 6 in. $\times$ 4 ft. 6 in.	\$ 11.44
2 windows, 2 ft. 6 in. $\times$ 5 ft. 6 in.	
2 windows, 2 ft. 6 in. $\times$ 3 ft. 9 in.	
2 pairs French windows (oak),	
4 ft. 6 in. × 7 ft. 6 in.	, at \$18.24 each 36.48
1 window, 3 ft. 4 in. $\times$ 5 ft. 6 in.	(oak finish) 16.57
	Carried forward \$3,550.91



Brought forward \$3,	550 91
1 window, 3 ft. 4 in. × 5 ft. 6 in. (birch finish)	16.57
1 window, 2 ft. 6 in. × 5 ft. 6 in. (birch finish)	14.45
2 windows, 3 ft. 4 in. × 5 ft. 5 in. (whitewood), at	11.10
	26.66
4 windows, 2 ft. 6 in. $\times$ 4 ft. 6 in. (N. C. pine), at	
	45.76
FRONT DOOR, with side and top lights—	
3 ft. 3 in. × 7 ft. 6 in.	56.33
Rear Door—	
2 ft. 10 in. × 7 ft. 6 in	13.46
Cellar Sashes—	10.10
12, at \$3.25 each	39.00
Inside Finish—	00.00
Coal bins in basement, 240 sq. ft.	
Studding 240 sq. ft. at \$3.00 per square \$ 7.20	
Boarding 240 " "\$4.75 " " 11.40	
Labor on 2 doors, one day	21.85
COLD-AIR BOX—	21.00
3 ft. 0 in. × 1 ft. 0 in., 25 ft. long, at \$.62 per linear ft	15.50
BASEMENT PARTITIONS—	10.00
46 ft. 0 in. × 8 ft. 0 in., 368 sq. ft., at \$8.75 per square	32.20
3 doors, at \$8.87 each	26.61
$67\frac{1}{2}$ ft. shelving, at \$.15 per ft.	10.12
1 door to bulkhead	10.00
First Story—	10.00
1 door, 2 ft. 8 in. $\times$ 7 ft. 6 in. (whitewood and birch finish)	20.67
1 pair sliding doors (whitewood and birch finish)	53.52
40 ft. birch base at \$.20 per ft	8.00
1 door, 3 ft. 3 in. × 7 ft. 6 in. (whitewood and oak)	22.67
1 door, 2 ft. 10 in. × 7 ft. 6 in. (whitewood and oak)	20.67
Wood Cornice in Dining Room— .	
56 ft., 6 in. × 6 in. (birch), at \$.48 per ft\$26.88	
56 ft. picture moulding, at \$.06 per ft 3.36	30.24
Wood Cornice in Library—	
82 ft., 6 in. × 6 in. (oak), at \$.48 per ft\$39.36	
[2] 그리고 : [2] [2] [2] [2] [2] [2] [2] [2] [2] [2]	,035.19

Brought forward \$39.36 \$4,035.19
82 ft. picture moulding, at \$.06 per ft
Oak Base—
72 ft. at \$.20 per ft
1 door, 3 ft. 0 in. $\times$ 7 ft. 6 in (whitewood)
VESTIBULE Door, side lights and top light, same as front door. 56.33
Whitewood Base, 101 ft., at \$.10 per ft
5 doors (N. C. pine), at \$9.48 each 47.40
CHINA CLOSET FINISH
Pantry
KITCHEN AND BACK ENTRY SHEATHING—
65 linear ft., at \$.40 per ft
Mantels—
Allowance
Labor of setting
Second Story—
16 doors stock, at \$9.48 each\$151.68
1 arch in hall
2 wood columns, at \$10.00 each
5 closets, at \$3.50 each
1 linen closet
1 linen closet
THIRD STORY—
2 doors, finished one side, at \$7.04 each \$ 14.08
1 closet door
Tank
Finished floor, 100 sq. ft
Conductors—
120 ft., at \$.13 per ft., put up
Freight, Fares and Expenses
Insurance         10.00           Total cost of Carpenter Work         \$4,928.34
Total cost of Carpenter Work



FRAMING-PLAN- OF-ROOF"Scale of LILL LILL feet."

# STAIRS

Front Stairs—	
128 ft. spruce, at \$30 per M 3 . 84	
120 ft. whitewood, at \$70 per M 8.40	
85 ft. quartered oak, at \$150 per M: 12.75	
30 ft. mahogany rail and turn 24.00	
5 paneled posts at \$5.00 each	
105 balusters at \$.15 each	
11 nosings at \$.06 each	
25 scotias at \$.03 each	
Nails, glue, etc	
Labor 56.00	\$148.15
BACK STAIRS—	
First Flight—	
55 ft. spruce, at \$30 per M \$ 1.65	
105 ft. N. C. pine, at \$60 per M 6.30	
16 scotias at \$.03 each	
Nails, etc	
Labor	25.18
Second Flight—	
54 ft. spruce, at \$30 per M \$ 1.62	
110 ft. N. C. pine, at \$60 per M 6.60	
17 scotias at \$.03 each	
Nails, etc	
1 post	
4 ft. rail, at \$.12½ per ft	
12 balusters at $\$.06\frac{1}{4}$ each	
Labor	28.48
Cellar Stairs—	
40 ft. spruce, at \$30 per M \$ 1.20	
75 ft. N. C. pine, at \$60 per M 4 . 50	
Post	
Rail	
Labor 5.00	12.40
	\$214.21
Framing	
Total cost of Stairs	
1 Otal cost of Stairs	. φ210.21

# **HARDWARE**

Note.—This estimate is based upon a fair quality of hardware, the butts being of bronze-plated steel, the knobs of struck-up bronze metal, with rose and escutcheon combined; the sash fasts of solid bronze metal, also lifts and catches.

### BASEMENT

Bulkhead, Outside—		
2 pairs extra heavy galv. T hinges, 8-inch at		
\$.85 each	\$1.70	
2 hooks and staples, 5-inch, at\$.10 each	.20	
Labor	1.00	
Bulkhead, Inside—		
1 pair heavy T hinges, 8-inch	.15	
I thumb-latch	.10	
Labor	.50	
Three Doors—		
3 pairs butts, $3\frac{1}{2} \times 3\frac{1}{2}$ -inch, at\$.15 each	.45	
3 sets locks at	1.35	
Labor	1.50	
HINGED WINDOWS—		
12 pairs butts, 1 <sup>1</sup> / <sub>4</sub> -inch, at \$.06 each	.72	
12 hooks and eyes, at\$.02 each	.24	
12 buttons, at	.24	
Labor	1.50	\$ 9.65
FIRST FLOOR		
Entrance Door—		
$1\frac{1}{2}$ pairs butts, $4\frac{1}{2} \times 4\frac{1}{2}$ -inch, at\$.38 each	\$ .57	
1 set locks, bronze metal	9.50	
Labor	2.00	
Seven Inside Doors, Front—		
7 pairs butts, $3\frac{1}{2} \times 3\frac{1}{2}$ -inch, at\$.30 each	2.10	
7 sets locks at	7.00	
Labor	5.25	
Carried forward §	\$26.42	\$9.65




Fig. 14.

Brought forward	\$26.42	\$9.65
SIDE ENTRANCE DOOR—		
$1\frac{1}{2}$ pairs butts, $4\frac{1}{2} \times 4\frac{1}{2}$ -inch, at\$.38 each	.57	
1 set locks	2.25	
Labor	1.00	
ONE PAIR SLIDING DOORS, 5 ft. 0 in.—		
1 set hangers, 5 ft. 0 in, Double	3.50	
1 set S. D. locks	2.50	
Labor	2.00	
SIX INSIDE BACK PORTIONS—		
6 sets lock sat	2.70	
6 pairs butts, $3\frac{1}{2} \times 3\frac{1}{2}$ -inch, at\$.15 each	.90	
Labor	4.00	
Back Doors—		
$-1\frac{1}{2}$ pairs butts, $4\frac{1}{2} \times 4\frac{1}{2}$ -inch, at\$.20 each	.30	
1 set locks	2.25	
Labor	1.00	
Ice-Chest Door—	1.00	
1 pair butts, 3 × 3-inch	.40	
1 IH lever, galvanized	.60	
1 brass hasp and padlock.	1.50	
Labor	.50	
	.00	
CHINA CLOSET—		
2 pairs glass doors—	70	
2 pairs butts, $2\frac{1}{2} \times 2\frac{1}{2}$ -inch, at\$ .26 each	.52	
2 elbow catches, at	.12	
2 cupboard catches, at \$.15 each	.30	
1 pair cupboard doors—	200	
, 2 pairs butts, $2\frac{1}{2} \times 2\frac{1}{2}$ -inch, at\$.10 each	.20	
1 elbow catch	• .06	
1 cupboard catch	.15	
20 drawer-pulls, at \$ .06 each	1.20	
Labor	2.50	
PANTRY—		
4 cupboard doors—	40	
4 pairs butts, $2\frac{1}{2} \times 2\frac{1}{2}$ -inch, at\$ .10 each		00 45
Carried forward	\$57.84	\$9.65

	D	7 01	@O CE
4 boom bootshop of	Brought forward \$5	.60	\$9.65
4 cupboard catches, at		.75	
10 drawer-pulls, at		.60	
		2.00	
Labor		2.00	
15 sash fasts, at	© 20 aaah	1 50	
		4.50 $1.80$	
30 sash lifts, at		7.50	
Labor		7.50	
CASEMENT WINDOWS,	Ø 701	0.00	
4 pairs butts, 3 × 3-inch, at		2.00 $2.00$	
2 pairs flush bolts, at			
2 casement fasts, at		.90	@O1 10
Labor		1.00	\$81.49
SECOND	FLOOR		
Sixteen Doors—			
16 pairs butts, $3\frac{1}{2} \times 3\frac{1}{2}$ -inch, at			
16 sets locks, at			
Labor		0.40	
Windows—			
14 sash fasts, at	\$.30 each	4.20	
1 sash fast		.35	
28 sash lifts, at	\$.06 each	1.68	
2 sash lifts, at	\$.10 each	.20	
Labor		7.00	
SIX DRAWERS IN LINEN CLOSET—			
12 drawer-pulls, at	\$.06 each	.72	
Labor		.25	\$44.00
Ватнгоом—		-	
1 pair butts, $3\frac{1}{2} \times 3\frac{1}{2}$ -inch (nick	kel-plate)	40	
1 set locks (nickel-plate)			
Labor			\$ 2.40
AT			
Two Doors—			
2 pairs butts, $3\frac{1}{2} \times 3\frac{1}{2}$ -inch, at	\$.12 each\$.	24	4
2 sets locks, at	\$.45 each	90	
Labor			
	Carried forward \$2		\$137.54
	,		




Fig. 15.




Fig. 16.

Brought forward \$2.14	\$137.54
Two Low Doors—	
2 pairs butts, $2\frac{1}{2} \times 2\frac{1}{2}$ -inch, at\$.10 each20	
2 cupboard turns, at	
Labor1.00	
Windows—	
8 sash fasts, at	
16 sash lifts, at	
Labor	
6 doz. H. & C. hooks, $639\frac{1}{2}$ , at \$.50 doz 3.00	
3 doz. base knobs, at	
Labor	\$ 17.95
Total cost of Hardware put on	\$155.49
HEATING	
FURNACE—	
1 No. 28 Crawford furnace (28-in. firepot) \$125.00	
22 ft. 8-in. galv. iron smoke-pipe, 55 lbs.,	
at\$.09 lb. 4.95	
REGISTERS—	
$1.14 \times 18$ -in. register, stone, box and netting, 4.72	
$4.9 \times 12$ -in. registers, stone, box and netting,	
at\$1.57 each 6.28	
$4.8 \times 10$ -in. registers, stone, box and netting,	
at \$1.19 each 4.76	
$4.8 \times 10$ -in. registers, stone, box and netting,	
at\$1.15 each 4.60	
PIPING, including dampers, collars, and elbows—	
12 ft. 14-in. tin pipe, at \$ . 27 per ft 3 . 24	
64 ft. 9-in. " at\$.16 " " 10.24	
278 ft. 7-in. " " at\$.10 " " 27.80	
Covering for Risers (6 lbs. asbestos paper per pipe)—	
5 risers, 30 lbs., at \$.05 lb 1.50	
PLASTERING RINGS IN CELLAR—	
For 13 pipes at \$.20 each	
\$ 195.69	
Office expense and profit 48.92	\$244.61
Carried forward	\$244.61




Fig. 17.

Brought forward		\$244.61
Labor—		
Measuring and laying out risers, man 1 day .	\$4.80	
Erecting risers, man 2 days, helper 1 day	12.00	
Laying out and erecting cellar pipes and fur-		
• nace, man 3 days, helper 2 days	19.20	
Finishing, man 1 day	4.80	
Carting and expenses	10.00	50.80
Total cost of Heating Apparatus		\$ 295.41
PLUMBING		
Waste and Soil Pipes—		
2 4-in. lead bends, at \$1.10 each	\$2.20	
2 4-in. sleeves, at \$.65 each	1.30	
5 2-in. " at \$.28 each	1.40	
$2 \cdot 3 \times 2$ -in. sleeves, at \$ .45 each	.90	
$1$ $1\frac{1}{2}$ -in. Pemberton trap	6.80	
30 lbs. solder, wiping, at \$.25 lb	7.50	
2 trap plugs, at \$.42 each	.84	
2 6-in. traps, at \$2.35 each	4.70	
1 6-in. cesspool	3.00	
4 1½-inch solder nipples, at \$.15 each	.60	
1 4-in. roof flashing	1.35	
Soil pipe	47.87	
15 ft. $1\frac{1}{2}$ -in. lead pipe, No. 55	3.24	
50ft 2 in incoming)	0.00	
40 ft. 1½-in. " " (	8.96	
Soil fittings, $\frac{1}{3}$ cost of pipe	15.96	
Cast-iron fittings, 20 per cent	1.79	\$ 108.41
Miscellaneous Fittings—		
3 4-in. b ass C. O	\$ 2.70	
1 5-in. brass C. O	1.50	
Refrigerator waste	12.50	
Local vents	12.00	
1 ball-cock	1.25	
2 sill cocks	2.00	
Tank overflow	6.50	
4 <sup>3</sup> -inch S. & W. cocks	3.24	
Carried forward	\$41.69	\$108.41

Brought forward	\$ 41.69	\$ 108.41
1 boiler valve and chain	.70	
25 lbs. tinned copper, at \$.32 lb	8.00	
6 3-part hangers, brass	6.30	
2 <sup>3</sup> / <sub>4</sub> -in. hose bibs	1.50	
$3\frac{3}{4}$ -inch plain bibs	2.10	
Street connections	55.00	
¹ 1 lb. putty	.05	
2 lbs. grafting wax	.50	
Calking lead, 380 lbs	22.80	
Oakum	1.60	\$ 140.24
		W 110.21
FIXTURES—		
1 36 x 24 x 8-in. sink, 12-in. back	\$11.40	
1 24 x 14-in. pantry sink	14.00	
1 pair pantry cocks	3.60	
2 24 x 48-in. trays, 12-in. back	14.10	
15-ft. bathtub, complete	41.00	
1 lavatory, complete	32.50	
1 water-closet, complete	60.00	
1 40-gallon boiler	16.75	
1 " " stand	.85	
12 lbs. fine solder	3.12	
Clamps and hooks	2.70	
Tinned tacks	.15	
Fuel	1.95	\$ 202.12
Supplies and Labor—		
126 ft. <sup>3</sup> / <sub>4</sub> -inch galv. water pipe	\$4.41	
22 ft. ½-inch " " "	.62	
Fittings, $\frac{1}{3}$ cost of pipe	1.67	
74 ft. <sup>3</sup> -in. brass		
$56 \text{ ft.} \frac{1}{2}\text{-in.}$ "	39.73	
Fittings, 20 per cent	7.95	
Painting of iron pipes	9.75	
Stop-cocks	3.54	
Sink and tray legs	4.72	
Lead, oil, etc.	.65	
Carried forward	\$ 73.04	\$ 450.77

	Brought forward \$ 73.04	\$	450.77
Clar	mping brass and screws	**	
	age and fares		
	or, 40 days, at \$6.00 per day: 240.00		318.29
		\$	769.06
	Profit, 10 per cent		76.90
	Total cost of Plumbing	.\$	845.96
	ELECTRIC WIRING		
75 64	No. 4 S. B. R.C. wire		@ 4 OO
			\$ 4.80
150 ft.			4.26
40 30	Large porcelain tubes, 5 cents		2.00
	knobs, 5 cents		1.50
1	3-pole 50-amp. fused switch		1.50
1-	Main cabinet (meter)		3.50
	8-circuit cut-out panel		16.00
2,500 ft.	No. 14 S.B. R.C. wire.		28.60
500 ft.	1 4-in. circular loom		20.00
800	5½ knobs		3.20
1,600	5-in. porcelain tubes		4.00
100	Fire stops		9.00
100	12-in. porcelain tubes		10.00
18	Ceiling boxes		1.80
30	Bracket boxes		3.00
. 11	Switch boxes		2.20
11	***************************************		12.10
	Labor on No. 14 wire.		55.00
	mains		15.00
	IIIIISII		15.00
	Teaming and freight		5.00
	Sundries		5.00
	Nails, leatherheads, etc	-	3.00
			225.46
	Office expense, 10 per cent	_	22.55
			248.01
	Profit, 20 per cent		49.60
	Total cost of Electric Wiring	.\$	297.61

Note.—This estimate is figured on outlet boxes at all outlets; and includes a main cabinet and main switch to connect with the meter and to cover the meter, on an eight-circuit panel-board, which allows one spare circuit. The panel-board is to be made of slate, with slate gutters and linings, with good wood door and trim.

The labor is estimated on wages being \$3.60 per day for a journeyman, and \$2.00 per day for helper. This price is above that paid in small places, but is below what is paid in some cities.

#### **ELECTRIC LIGHTING FIXTURES**

Note.—While the electric lighting fixtures are not generally made a part of the building contract, it may be worth while to consider them in relation to the cost of the house; although, as has been stated, there is such a wide range in design and cost, as well as in personal preference, that any data given can be at best only approximate.

The following estimate is based upon simple designs of moderate cost in "old brass" finish:

#### FIRST STORY LIVING ROOM-1 4-light electrolier ...... \$17.50 4 1-light wall brackets, at \$3.25 each..... 13.00 HALL-2 2-light ceiling pieces, at \$2.50 each ..... 5.00 VESTIBULE— 1 3-light cluster ...... 5.00 PORCH-1.75 PARLOR-17.50 2 1 " wall brackets..... 6.50 DINING ROOM-1 4-light electrolier ..... 10.00 2 1 " wall brackets..... 5.00 CHINA CLOSET, REAR HALL, KITCHEN-3 1-light ceiling-pieces, at \$.75 each..... 2.25 2.70 Carried forward \$86.20

20
75
35
75
00
10
00
.0
50
35
).)
35
35
35
.5
0
00
0
0
0
0
0
0
$\vec{0}$

Brought forward	\$239.10
54 yds. two coats metallic paint, upper side tin	
roofs, at \$.15 yd	8.10
62 yds. two coats oiling on floors, porch, and piazza, at	
\$.10 yd	6.20
Interior Painting—	
166 yds. filling, staining, and shellacing, and two	
coats hard oil finish, at \$.20 yd	\$33.20
245 yds. filling and two coats spar varnish, first coat	
rubbed, at \$.25 yd	61.25
403 yds. one coat shellac, three of paint, two coats	
zinc and white varnish. Rubbed with pumice and	
water, ivory white finish, at \$.80 yd	322.40
294 yds. treat with potash, one oil filler, clean, four	
coats shellac, last coat rubbed with pumice and oil,	
oak and birch, at \$.35 yd	102.90
109 yds. filling, four coats shellac, last coat rubbed	
with pumice and oil, floors at \$.30 yd	32.70
114 yds. size and three coats paint, last coat with	
varnish, walls, at \$.20 yd	22.80
5 yds. three coats paint and one enamel gloss, bath-	
tub, at \$.25 yd	1.25
100 yds. three coats paint, last with zinc, flat, white-	07.00
wood, at \$.25 yd	25.00
10 yds. one coat shellac on pipes, at \$.10 yd	1.00
299 yds. size and tint in water-colors, ceilings, at	11 05
\$.15 yd	44.85
Total cost of Fainting	900.10
GENERAL SUMMARY	
Batter-Boards and Water Supply\$ 25.00	
Excavation	
Stonework, Cesspools, and Drains 754.15	
Chimneys and Brickwork 281.50	
Concreting 88.20	
Plastering 544.40	
Carpenter Work	
Carried forward \$6,884.09	

## -DETAILS-OF- TRIM-ON-FIRST-FLOOR-

·REJIDENCE-AT-RIDGEDALE-MO-·FOR-GEORGE-A-JONES-EVQ-




Fig. 18.

	Brought	forward	\$6,884.09
Stairs			216.21
Hardware			155.49
Heating			295.41
Plumbing			845.96
Electric Wiring			297.61
Electric Fixtures			152.00
Painting			900.75
		Total,	\$9,747.52

### SCHEDULES

#### ANALYSIS OF CARPENTER WORK

Following is a section devoted to the analysis of the different portions of carpenter work in the foregoing estimate. These show how the prices are obtained, and will be very useful for comparison, as the changes in cost of parts can be noted and kept up to date.

First Floor, price per square of 100 sq. ft., including the floor beams, bridging, and under floors, but no furring for plaster— Joists,  $2 \times 10$ -in., 16 inches on centers ..........\$3.25 Labor ..... 1.50 Nails.... .10 Bridging..... .50 Under floor, hemlock, at \$24.00..... 2.30 Waste, one-third..... .80 Labor ..... .75 Nails ..... \$ 9.35 .15 Hard Pine Upper Floor, per square of 100 sq. ft.— Stock ...... \$6.00 Waste, one-third..... 2.00 2.25 Labor ...... .25 \$10.50 Quartered Oak Upper Floor, per square of 100 sq. ft.-Waste ..... \$20.05

Porch or Veranda Floor, per square of 100 sq. ft.—	
Joists, $2 \times 8$ -in., 16 inches on centers \$2.60	
Labor	
Hard pine flooring, at \$55 5.50	
Waste 1.80	
Labor	
Nails	\$12.35
Second Floor, per square of 100 sq. ft.—	
Joists, $2 \times 10$ -in., 16 inches on centers	
Labor	
Bridging	
Furring	
Under-floor stock 2.30	
Waste, one-third	
Labor	
Nails	
Upper-floor stock 4.00	
Waste	
Labor	
Nails	\$18.00
Third Floor, per square of 100 sq. ft.—	
Joists, $2 \times 8$ -in., 16 inches on centers \$ 2.60	
Labor	
Under floor 4.00	
Furring	
Bridging	\$10.10
Dridging	ф10.10
Shingled Roof, per square of 100 sq. ft—	
Rafters, $2 \times 7$ -in, 20 inches on centers\$ 2.17	
Labor 2.25	
Matched spruce boarding 2.50	
Waste, one-third	
Labor	
Nails	
Shingles 4.00	
Labor 3.25	
Nails	\$16.67

T: 1 D - f f 100 f	
Tinned Roof, per square of 100 sq. ft.—	
Rafters, $2 \times 7$ -in., 20 inches on centers \$ 2.17	
Labor	
Matched boarding, as above 4.75	
Paper	
Tinning	\$20.92
Wall Frame and Boarding, per square of 100 sq. ft.—	
Studding, $2 \times 4$ -in., 16 inches on centers\$ 4.00	
Boarding	
Waste	
Labor. 1.00	
Nails	\$ 8.30
Inside Studding, per square of 100 sq. ft.—	
Stock, 2x4-in., 16 inches on centers \$ 1.30	
Waste, one-half stock	
Labor	
Nails	
Grounds and beads	\$ 4.00
Clapboarding, per square of 100 sq. ft.—	
Clapboards, 80, at \$.05 each\$ 4.00	
Labor 3.25	
Paper	
Nails	\$ 7.95
Main Cornice, per linear foot—	
Gutter, per ft\$ .12	
Upper fascia	
Fillet	
Lower fascia	
Planceer	
Bed-mould	
Frieze	
Architrave moulding	
Brackets	
Labor	
Rough furring	\$ 1.25
Piazza Cornice, per linear foot—	
Upper fascia \$ .03	La Ka
Carried forward \$ .03	




Fig. 19.

Brought forward \$ .03	
Gutter	
Lower fascia	
Fillet	
Planceer	
Bed-mould	
Brackets	
Frieze	
Architrave mould	
Soffit	
Inside frieze	
Labor	
Rough furring	\$ 2.00
Attic Windows, circular top, each—	
Frame\$ 6.00	
Sash	
Inside finish	
Weights and cord	
Labor	\$11.20
Second-Story Windows, 3 ft. 6 in. × 5 ft., each—	
Frame	
Sashes, 17½ sq. ft., at \$.20 per sq. ft \$ 3.50	
Blinds	
Blind fasts	
Inside finish	
Nails and screws	
Weights and cord	
Labor, 1 day	\$13.33
Inside Finish for Window, as above—	
Architrave, $21 \text{ ft., at } \$.03\frac{1}{2} \text{ per ft.} \dots \$.73$	
Back-band, 21 ft., at \$.03 " "	
Beads, 17 ft., at \$.02 " "	\$ 1.70
30 per cent off	.51
	\$ 1.19
Weights and Cord for Window, as above—	
Weights, $17\frac{1}{2}$ ft., 2 lbs. per ft., 35 lbs., at \$.01\frac{1}{4}	
per lb\$ .44	
Cord, 20 ft., at \$.01 per ft	\$ .64

Cost of Window, 2 ft. 6 in. x 4 ft. 6 in., each—	
Frame\$ 3.50	
Window, 11 <sup>1</sup> / <sub>4</sub> sq. ft., at \$.20 per sq. ft 2.25	
Blinds	
Blind fastenings	
Screws and nails	
Weight, $22\frac{1}{2}$ lbs., at \$.01\frac{1}{4} per lb	
Cord	
Inside Casing, 18 ft., at $\$.03\frac{1}{2}$ per ft	
Back-band, 18 ft., at \$.03 per ft	
Stop-beads, 14 ft., at \$.02 per ft	
Labor	\$11.88
French Windows, 4 ft. 6 in × 7 ft. 6 in., each—	
Frame \$ 5.00	
Sash, 4 ft. 6 in. × 7 ft. 6 in., 34 sq. ft., at \$.20 per	
sq. ft	
Astragal	
Nails and screws	
Inside finish	
Labor	\$18.24
Window, 3 ft. 4 in. $\times$ 5 ft. 6 in. (oak finish), each—	
Frame\$ 3.50	
Window, 18 sq. ft., at \$ .20 per sq. ft 3 .60	
Blinds	
Blind fasts	
Nails and screws	
Weights	
Finish (oak)	
Labor, $1\frac{1}{2}$ days. 4.88	\$16.57
Rear Door, 2 ft. 10 in. $\times$ 7 ft. 6 in.—	
Frame \$4.00	
Door, 21 sq. ft., at \$.25 per sq. ft	
Finish	
Labor 3.25	
Nails	\$13.46

Front Door, 3 ft. 3 in. $\times$ 7 ft. 6 in., with top and sin $Frame$ —	de lights—	
Sill, 7 ft., at \$ .25 per ft	\$1.75	
Jambs, 23 ft., at \$.07 per ft	1.61	
Mullions and transom bar, 20 ft., at \$.10\frac{1}{2}	1.01	
per ft	2.10	
Outside casing, 23 ft., at $\$.03\frac{1}{2}$ per ft	.81	
Mullion casing, 20 ft., at \$ $.02_{\frac{1}{10}}$ per ft	42	
Labor, ½ price of stock	3.32	
Labor, 2 price of stock		
Door, 3 ft., 3 in. × 7 ft. 6 in.—	\$10.01	
21 sq. ft., at \$ .25 per sq. ft	\$5.25	
Side-light panels, 6 ft., at \$.25 per ft	1.50	
3 sash rims, at \$.50 each	1.50	
Leaded glass, $10\frac{6}{5}$ sq. ft., at \$2.50 per sq. ft.	27:00	
Leaded glass, 10 f sq. 1t., at \$2.50 per sq. 1t.		
Inside Finish—	\$35.25	
Stop-beads	\$ .28	
Architrave, 24 ft., at $\$.04\frac{1}{2}$ per ft		
Labor, 3 days	9.75	
Labor, 5 days	-	
The table and of front does and from	\$11.11	#FC 97
Total cost of front door and frame		\$56.37
Door, 2 ft. 8 in. × 7 ft. 6 in. (N. C. pine)—		
Stock door	\$3.00	
Frame	1.25	
Threshold	.15	
Nails	.05	
Finish, $39\frac{1}{2}$ ft., at \$.04\frac{1}{2} per ft	1.78	
Labor	3.25	\$9.48
Pair of Sliding Doors, 6 ft. $\times$ 8 ft. (whitewood and	birch)—	
Doors, 48 sq. ft., at \$.50 per sq. ft	\$24.00	
Architrave, 24 ft., birch	2.34	
" 24 ft., whitewood	1.05	
Jambs, 22 ft., birch	1.82	
" 22 ft., whitewood	.85	
Grounds, 22 ft., birch	.50	
Carried forward	\$30.56	

Brought forward	l \$30.56	
Grounds, 22 ft., whitewood	.23	
Chafing strip, 22 ft., birch	33	
22 ft., whitewood	.15	
Astragal, birch and whitewood	1.50	
Sheathing pockets, 96 ft., at \$4.75 per square.	4.50	
Labor, 5 days' work	16.25	\$53.52

## Schedule of Rooms, and Memoranda from which Heating Estimate is Made Up

FIRST FLOOR ROOMS	SIZE	CONTAINS CU. FT.	DIVIDE BY	EQUALS	SIZE OF REGISTER	AREA OF PIPES	FEET OF TIN PIPE, INCLUD- ING ELBOWS
Living Room.	$14 \times 25 \times 9$	3,150	25	2 9-in. pipes	$2.9\times12$		34
		Add 40% for space above,					
Hall	$11 \times 25 \times 9$	3,465	25	14-in. "	$14\times18$	154	12
Parlor	$12\times14\times9$	1,512	25	9-in. "	$9 \times 12$	64	14
Dining Room.	$12\times14\times9$	1,512	25	9-in. "	$9 \times 12$	64	16
China Closet.	$7 \times 10 \times 9$			7-in. "	7×10	38	24
SECOND FLOOR	7						0
Bedroom	$11\times14\times8\frac{1}{2}$	1,309	35	7-in. "	8×10	38	38
"	$11\times14\times8\frac{1}{2}$	1,309	35	7-in. "	8×10	38	26
"	$11\times14\times8\frac{1}{2}$	1,309	35	7-in. "	8×10	38	40
	$11\times14\times8\frac{1}{2}$	1,309	35	7-in. "	8×10	38	40
Alcove	$6\times11\times8\frac{1}{2}$			7-in. "	7×10	38	32
Bathroom	$6\times10\times8\frac{1}{2}$			7-in. "	7×10	38	38
Rear Bedroom	$10\times13\times8\frac{1}{2}$	1,105	35	7-in. "	$7 \times 10$	38	40

Smoke pipe, 22 ft.—Heat-pipe area, 714 sq. in.—Cold-air box, 534 sq. in., or  $\frac{3}{4}$  of heat-pipe area.—Use 28-in. firepot furnace.

#### Location Sheet of Electric Outlets

LOCATION	CEILING	BRACKET	Sw.		TOTAL
Basement—				OUTLETS	LIGHTS
Passage	1				1
Furnace	1			1	1
Laundry		1		1	1
Furnace Room	2			2	2
	4	1		4	5
First Floor—	•	•			
Entry		1		1	1
Pantry	1			1	1
Kitchen	1	2	2	5	3
Porch	1		1	2	1
China Closet	1			1	1
Dining Room	1	2		3	8-
Parlor	1	2		3	10
Hall	1			1	1
Hall	1		2	- 3	2
Vestibule	1			1	1
Porch	1			1	1
Living Room	1	4	2	7	13
	11	11	7	29	43
Second Floor—					
Back Hall		1	2	3	1
Bedroom		1		1	1
Bath		1		1	1
Bedroom		3		3	3
"		3		3	3
Alcove		2		2	2
Front Hall	2		2	4	2
Bedroom		3		3	3
"		3		3	3
	2	17	4	23	19
Attic—					
Hall		1		1	1
Attic	1			1	1
	1	1		2	2

## INDEX

	Page
Approximate estimates	3
Area, definition of	6
Areas of solids	12
Back stairs	35
Bells	58
Bluestone	19
Board measure	24
Brickwork	19
cost of	19
mortar for	19
Calculating the frame	27
Carpenter work	24
Carpentry	24
Catalogues	2
Cellar columns.	23
Cellar doors	32
Cellar window	32
Chimneys	22
Composition roofs	45
Concrete	21
Conductors	45
Cost of excavating	15
Cost of frame	28
Cost of setting cut stone.	18
Covering or spreading power of typical paints	
on metal	49
on plaster	49
on wood.	48
Cubical contents, definition of	6
Cut nails in fair assortment, national list of extras for	40
Cut stone	16
cost of setting	18
Day's work for carpenter	35
Definitions	6
Drainage	55
Duplicate parts	2
Earthen drain pipe	23
Electric work	57
Estimate	
approximate	3

	Page
Estimate	
making-up of actual	59
of residence at Ridgedale, Mo	-100
Estimating	
by quantities	5
by the square	4
Excavating, cost of	15
Excavation	14
Exterior finish	37
Face bricks	20
Fixtures.	33
Floors	56
Flue lining	29 22
	22
calculating the	27
cost of	28
Front door.	31
Front stairs	- 34
Galvanized elbows	52
Galvanized smoke pipe	52
Gas fitting.	57
Granite	16
Gutters	45
Hardware	. 39
Heating	50
first floor	51
quantities	51
second floor	51
Hot water heating	53
Inside doors	31
Inside finish	33
Inside studding	30
Lathing	46
Limestone.	17
Linear dimension, definition of  Location sheet of electric outlets	108
Lumber, miscellaneous prices of.	26
Marble	18
Masons' supplies	22
Measure of lines and surfaces	8
Metal roofs	45
Nails	39
Outside walls	29
Painting	48
cost of	49
inside work	49
outside work	50

Painting	Page
cost of	
sanding	50
Percentage	2
Piazzas and porches	37
Pile foundations	15
Piping for heating, cost of	.52
Plasterer's work, rules governing	47
Plastering	45
Plumbing	54
Plumbing labor	57
Preparation for estimating	5
Prices	1
Profit	2
Quartered oak floor	31
Radiation	53
Registers	52
Rift hard pine upper floors	31
Roofing	
Rules and tables	7
Sandstone	18
Scale of wages	13
Schedules	
Seam-faced granite	19
Setting cut stone, cost of.	18
Shingles.	42
cost of	43
measuring for	43
quantities	43
Shingling outside walls	30
Slating	43
quantities.	44
Sliding doors.	32
Soil pipes	55
Solid contents	13
Solids, areas of	12
Stairs.	34
Standard vitrified pipe, net price of	23
Steam heating	53
Stone work	15
Switches	58
Tables	0.11
board measure	25
circles, areas of	12
cisterns, capacity of	56
of multiples	7, 10
Tiles	45
Tin, per sheet, cost of	52
Transportation	. 3

#### INDEX

	Page
Units	7
Vitrified pipe, net price of standard	23
Wages, scale of	
Water	55
Water supply	55
Window sets	
Windows of average size	30
Wire nails	



# ANNOUNCEMENT OF COMING BOOKS

## PRACTICAL AND SCIENTIFIC

CARPENTRY. By 6. Townsend. 150 pp., 224 illus. A working manual for Carpenters and Woodworkers in general. Nota theoretical treatise, but a practical working guide. Price, \$1.00

GAS ENGINES AND PRODUCERS. By Marks and Wver. 150 pp., 90 illus. Latest information in this rapidly developing field. For Engineers, Machinists, Automobilists. Price........\$1.00

ELECTRIC RAILWAYS. By J. R. Cravath. 150 pp., 103 illus. Trolley and third-rail systems, Electric Locomotive, etc. Price. \$1.00

FSTIMATING Reveal Nichols 140 pp. 35; illus

ESTIMATING. By Edward Nichols. 140 pp., 35 illus.
For all workers in Building trades. Tells how to estimate intelligently. Price...\$1.00

STAIR-BUILDING AND STEEL SQUARE. By Hodgson and Williams. 130 pp., 180 illus. Only up-to-date work on these subjects. Price......\$1.00


MECHANICAL DRAWING. By E. Kenison. 160 pp., 140 illus. Complete course in projections, shade lines, intersections and developments, lettering, with exercises and plates. Price \$1.00


POWER STATIONS AND TRANSMISSION. By 6.C. Shaad. 160 pp., 43 illus. For Electrical Workers. Up-to-date practice. Price \$1.00

SURVEYING. By Alfred E. Phillips. 200 pp. 133 illus. For Civil Engineers and Students. All details of field work explained. Price \$1.50

BUILDING SUPERINTENDENCE. By E. Nichols 200 pp., 250 illus. Costly mistakes occur through lack of attention at proper time, hurtful to Owner and discreditable to Architect and Builder. Gives thorough knowledge of methods and materials. Price............\$1.50

These volumes are handsomely bound in red art Vellum de Luxe, size 6½ x 9½ inches. Sent pepaid to any part of the world, on receipt of price. Remit by Draft, Postal Order, Express Order, or Registered Letter.





## THIS BOOK IS DUE ON THE LAST DATE STAMPED BELOW

## AN INITIAL FINE OF 25 CENTS

WILL BE ASSESSED FOR FAILURE TO RETURN THIS BOOK ON THE DATE DUE. THE PENALTY WILL INCREASE TO 50 CENTS ON THE FOURTH DAY AND TO \$1.00 ON THE SEVENTH DAY OVERDUE.

OVERDO	
SEP 26 1934	
OCT 11 1934	
NOV 16 1934	
22Jan'50AP	
10May 50C8	
27 Mar'57AS	
REC'D LD	
MAR 13 1957	
MAR 10 Mac	
REC'D LD	
MAY 23 1953 LD 21-100m-7,'33	
The second secon	

